



90° Connectors



Zinc die-cast. For aluminum and steel Flex • AC • AC90 • MCI • MCI-A cable.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
850†	00850	3/8	1/2	50	500	1.325	.360	1.800	.440-.750
851†	00851	1/2	1/2	25	250	1.835	.415	2.140	.635-1.085
852	00852	3/4	3/4	15	150	2.025	.475	2.380	.770-1.205
853	00853	1	1	10	50	2.560	.625	2.510	1.330-1.570
854	00854	1-1/4	1-1/4	5	25	3.160	.625	3.080	1.625-1.940
855	00855	1-1/2	1-1/2	1	10	4.875	.750	6.050	1.400-2.400
856	00856	2	2	1	10	4.875	.750	6.050	1.400-2.400
857†	00857	2-1/2	2-1/2	1	1	6.125	.875	7.187	2.450-2.975
858†	00858	3	3	1	1	6.700	1.031	7.875	2.950-3.450
859†	00859	3-1/2	3-1/2	1	1	7.500	1.031	9.400	3.275-3.950
8510†	08510	4	4	1	1	8.700	1.031	10.200	3.675-4.425

†Malleable.

‡Also for MCI-A cable. See page E-30 and E-31 for MCI-A cable ranges.

Refer to chart on page E-27 for list of cable types.

Concrete tight when taped.

