

TV Bridge™ III Kits



TVBR21K

TVBR22K

UL Listed kits are the easiest, fastest way to install a flat screen TV.

FEATURES AND BENEFITS

- UL Listed to meet NEC 400.7 (11) for interconnecting wiring between an existing receptacle and an inlet
- Pre-wired, fully assembled for fastest installation
- Mounting wing screws hold the boxes secure against the wall
- Plugs and connections stay inside the recessed boxes so TV mounts flush against the wall
- No mess! Wires stay hidden behind the wall

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION	UNIT PKG	STD PKG
TVBR21K	24220	Two-gang upper box, Single-gang lower box	1	1
TVBR22K	24222	Two-gang upper box, Two-gang lower box	1	1

PATENTED. OTHER PATENTS PENDING.



KIT CONTENTS

Pre-assembled UL Listed power cable with upper and lower mounting boxes with installed brush-style cable entry devices, (1) UL Listed 6 ft., 14 gauge power extension cord, (2) #8 x 1/2" pan head screws and template for cutouts

INSTALLATION INSTRUCTIONS



1. Determine box location, avoiding framing members and obstructions. Cut (2) openings, with the top in desired location for TV; the bottom directly below it, near an existing electrical outlet. (Templates supplied for cutouts.) Fish power cable through top hole to bottom hole.



2. Install upper mounting box in opening by tightening four flag screws.



3. Attach male end of power cable to back of lower mounting bracket using (2) #8 x 1/2" screws (provided).
4. Insert lower assembly into opening and tighten four flag screws to hold it to the wall.
5. Energize the TV Bridge III kit by plugging the supplied power extension cord into existing receptacle or surge suppressor, and male end of power cable.