
Low Profile TV Box™




For flush-to-the-wall tv installations on walls as shallow as 3/4". Non-metallic. Plugs stay inside box so TV mounts closer to the wall. Mounting wing screws hold box securely in the wall. For new work or retrofit.

CATALOG	UPC/DCI/NAED	DESCRIPTION	UNIT	STD	DIM	DIM	DIM
NUMBER	MFG #018997		PKG	PKG	A	B	C
TVL508	52307	5" x 8" power and/or low voltage box	1	4	10.210	7.561	1.852

*Add suffix "GC" to Catalog # when ordering in Canada to include grounding clip, for example TVL508GC. **PATENTED.**





INSTALLATION INSTRUCTIONS











- After locating position of TV and installing mounting bracket, cut holes for upper and lower boxes in a clear space within the same stud bay.
- 2. Position lower box so that supplied cord reaches existing receptacle (or power conditioner). Feed NM cable connector from lower box. behind the wall, to upper box opening. Low voltage cable and speaker wire may also be pulled at this time.
- **3.** Install box/power cord assembly by tightening four wing screws.
- **4.** Install trim plate. Pull NM cable through connector. Install box in hole by tightening wing screws (see 3).
- **5.** Attach electrical receptacle to receptacle mounting bracket.
- **6.** Attach receptacle mounting bracket to box.