

SKU: CN2P24040

2 Pole Contactor 240V, 40A

Features:

- Series: CN Series Definite Purpose Contactors
- Compact HVAC/R definite-purpose design
- Class F high-temperature insulation
- Quick-connect coil terminals for easy wiring
- Suitable for compressors, fans, and resistive loads

Materials:

Thermal Ratings

- Insulation Class: Class F (155°C / 311°F)
- Ambient Operating Temperature: -40°C to 65°C (-40°F to 150°F)

Terminals & Connection:

- Line & Load Terminals: Box Lug
- Wire Size Compatibility: AWG 14–4 Cu
- Terminal Tightening Torque: 40 in-lbs

Coil & Power Connections

- Coil Terminals: Dual .250" QC
- Power Terminals: Dual or Quad .250" QC

Additional Features

- Arc Cover: Standard on 40A models

Certifications/Listings/Approvals:

Standards Met:


- UL508
- ARI 780/790

Certificates

- UL-E246810
- CSA-256361
- CCC-2013010304614127
- Semko/CE File No. EN60947-4-1:2010

Compliance: RoHS

Class 3211 04/ 3211 84; Class NLDX2/ NLDX8



Electrical Ratings:

Contactor Technical Data

Model	Full Load Amps	Locked Rotor Amps			Restrictive Amp Rating	Max Horsepower HP		Coil Voltage	Approx Unit Weight
						Single Phase			
		240-277v	480v	600v		120v	240v		
CN2P24040	40A	240A	200A	160A	40A	2HP	6HP	240v	0.6 lb

Coil Technical Data

Nominal Coil Voltage	Min Pickup Volts	Drop-Out Volts Range	Nominal Inrush VA @ 50Hz	Nominal Inrush VA @ 60Hz	Nominal Sealed VA @ 50Hz	Nominal Sealed VA @ 60Hz	Nominal DC Resistance-Ohms	Max Coil Voltage
240v	177v	40-140v	22A	20A	5.5A	4.5A	1000Ω	264v

Product Offerings Designation & Dimensions:

