



14-SWP / 14-GSWP SERIES STRING WOUND POLYPROPYLENE FILTER CARTRIDGE

Application:

- Used in a wide range of filtering applications, polypropylene has a broad chemical compatibility and has excellent resistance to micro-organisms.
- Suitable for the filtration of potable water and liquids, petroleum or vegetable oils, strong acids, concentrated alkalis.

Specification:

- Manufactured from FDA grade polypropylene
- Diagonally wound pattern provides maximum surface area for efficient particle filtration
- Max Temperature Rating: 120°F (49°C)
- Filter media: Polypropylene
- Filter core: Polypropylene

Certification:

- NSF/ANSI Standard 42 Certified



This Filter Cartridge is Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only.



Third Party
Certified to
NSF / ANSI 372



COMMITTED TO EXCELLENCE SINCE 1955

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com



14-SWP / 14-GSWP SERIES STRING WOUND POLYPROPYLENE FILTER CARTRIDGE

DIMENSIONS						
Part No.	Inner Diameter	Outer Diameter	Length	Micron	Flow Rate	Weight
	inches	inches	inches	Rating	PSI Drop @ GPM	grams
Standard						
14-SWP1-01	1"	2-1/2"	9-7/8"	1	1 PSI @ 3 gpm	197
14-SWP1-05	1"	2-1/2"	9-7/8"	5	1 PSI @ 5 gpm	197
14-SWP1-05-2PK	1"	2-1/2"	9-7/8"	5	1 PSI @ 5 gpm	197
14-SWP1-10	1"	2-1/2"	9-7/8"	10	1 PSI @ 10 gpm	181
14-SWP1-25	1"	2-1/2"	9-7/8"	25	1 PSI @ 15 gpm	181
14-SWP1-25-2PK	1"	2-1/2"	9-7/8"	25	1 PSI @ 15 gpm	181
14-SWP1-50	1"	2-1/2"	9-7/8"	50	1 PSI @ 20 gpm	181
14-SWP2-01	1"	2-1/2"	20"	1	1 PSI @ 6 gpm	393
14-SWP2-05	1"	2-1/2"	20"	5	1 PSI @ 10 gpm	393
14-SWP2-10	1"	2-1/2"	20"	10	1 PSI @ 20 gpm	363
14-SWP2-25	1"	2-1/2"	20"	25	1 PSI @ 30 gpm	363
14-SWP2-50	1"	2-1/2"	20"	50	1 PSI @ 50 gpm	363
Giant						
14-GSWP1-01	1"	4-1/2"	10"	1	1 PSI @ 8 gpm	734
14-GSWP1-05	1"	4-1/2"	10"	5	1 PSI @ 15 gpm	734
14-GSWP1-10	1"	4-1/2"	10"	10	1 PSI @ 20 gpm	734
14-GSWP1-25	1"	4-1/2"	10"	25	1 PSI @ 25 gpm	680
14-GSWP1-50	1"	4-1/2"	10"	50	1 PSI @ 35 gpm	680
14-GSWP2-01	1"	4-1/2"	20"	1	1 PSI @ 16 gpm	1700
14-GSWP2-05	1"	4-1/2"	20"	5	1 PSI @ 30 gpm	1588
14-GSWP2-10	1"	4-1/2"	20"	10	1 PSI @ 40 gpm	1588
14-GSWP2-25	1"	4-1/2"	20"	25	1 PSI @ 50 gpm	1475
14-GSWP2-50	1"	4-1/2"	20"	50	1 PSI @ 65 gpm	1475

NSF/ANSI Standard 42 - Drinking Water Treatment Units (Aesthetic Effects) - Covers point-of-use and point-of-entry (POU / POE) systems designed to reduce specific aesthetic, or non-health effects contaminants (chlorine, TDS, particulates) that may be found in drinking water that is considered to be microbiologically safe.

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.



COMMITTED TO EXCELLENCE SINCE 1955

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com