


# BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

## NO LEAD SOLID BRASS TANK TEES




PART NO.	TANK CONNECTION	IN-LINE CONNECTION	CENTRE END LENGTH	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY CTN	CASE
2-07TK-54S-2NL	1-1/4" MPT	1" MPT X 3/4" FPT	3"	(2) 1/2" FPT	(2) 1/4" FPT	5	40
2-07TK-25SF-2NL	1" FPT	1" MPT x 3/4" FPT	3-5/8"	(2) 1/2" FPT	(2) 1/4" FPT	4	32
2-07TK-25S-2NL	1" MPT	1" MPT x 3/4" FPT	3-5/8"	(2) 1/2"	(2) 1/4"	5	40
2-07TK-25-2NL	1" MPT	1" MPT x 3/4" FPT	10"	(2) 1/2"	(2) 1/4"	2	24
2-07TK-25-1NL	1" MPT	1" MPT x 3/4" FPT	10"	(1) 1/2"	(2) 1/4"	2	24
2-07TK-14X1-2NL	1" MPT	1" MPT x 3/4" FPT	13"	(2) 1/2"	(2) 1/4"	2	20
2-07TK-13SF-2NL	1-1/4" FPT	1-1/4" MPT x 1" FPT	3-5/8"	(2) 3/4" FPT	(2) 1/4" FPT	4	32
2-07TK-13S-2NL	1-1/4" MPT	1-1/4" MPT x 1" FPT	3-3/8"	(2) 3/4"	(2) 1/4"	4	32
2-07TK-13-2NL	1-1/4" MPT	1-1/4" MPT x 1" FPT	13"	(2) 3/4"	(2) 1/4"	2	12

## NO LEAD CENTER END WELLMATE TANK TEE

Specially designed for the WellMate "QC" Quick Connect Tank series

- Alignment tabs interlock with tank connection to keep tee in perfect position
- Leg length allows replacement of pressure switch without hitting the tank (no need to disassemble the tee from the tank)




PART NO.	TANK CONNECTION	LINE CONNECTION	CENTRE END LEN.	DRAIN/RELIEF PORTS	GAUGE & PRESSURE SWITCH PORTS	QUANTITY CTN	CASE
07TK-25S-2-WMNL	Special Male Q.C. O-Ring Union c/w alignment tabs	1" MPT X 3/4" FPT	4-1/8"	(2) 1/2" FPT	(2) 1/4" FPT	2	24
07TK-13S-2-WMNL	Special Male Q.C. O-Ring Union c/w alignment tabs	1-1/4" MPT X 1" FPT	6"	(2) 3/4" FPT	(2) 1/4" FPT	2	24


## NO LEAD BRASS O-RING UNION TANK TEES



2-07TKO-25S-2UNL




2-07TKO-25-2UNL



PART NO.	TANK CONN.	IN-LINE CONN.	CENTRE END LEN.	DRAIN/RELIEF PORTS	ACCESSORY PORTS	O-RING	QUANTITY CTN	CASE
2-07TKO-25S-2UNL	1" MPT	1" MPT x 3/4" FPT	4-3/8"	(2) 1/2"	(2) 1/4"		4	24
2-07TKO-25-2UNL	1" MPT	1" MPT x 3/4" FPT	10"	(2) 1/2"	(2) 1/4"		2	20
2-07TKO-25-1UNL	1" MPT	1" MPT x 3/4" FPT	10"	(1) 1/2"	(2) 1/4"			
2-07TKO-14X1-2UNL	1" MPT	1" MPT x 3/4" FPT	13"	(2) 1/2"	(2) 1/4"		2	16
2-07TKO-13S-2UNL	1-1/4" MPT	1-1/4" MPT x 1" FPT	4-1/2"	(2) 3/4"	(2) 1/4"		4	24
2-07TKO-13-2UNL	1-1/4" MPT	1-1/4" MPT x 1" FPT	13"	(2) 3/4"	(2) 1/4"		2	12
2-07TKO-8-2UNL	1" MPT	1" MPT x 3/4" FPT	7-1/2"	(2) 1/2"	(2) 1/4"		2	20

## NO LEAD BRASS FEMALE UNION TANK TEES

- 1" or 1-1/4" FPT brass union nut c/w American Standard Buno-N ring for positive seal to any 1" or 1-1/4" MPT tank connection.
- These tank tees can be used with Flexcon's "FlexLite" tank and the Well Mate tanks or any other tank on the market with a 1" or 1-1/4" male connection.
- Replacement O-ring can be purchased at local industrial/hardware store
  - 1" = uses AS 568-212 O-ring
  - 1-1/4" = uses AS 568-320 O-ring



PART NO.	TANK CONNECTION	IN-LINE CONNECTION	CENTRE END LENGTH	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY CTN	CASE
2-07TK-25SF-2UNL	1" FPT Union	1" MPT x 3/4" FPT	3"	(2) 1/2" FPT	(2) 1/4" FPT	4	32
2-07TK-13SF-2UNL	1-1/4" FPT Union	1-1/4" MPT x 1" FPT	3"	(2) 3/4" FPT	(2) 1/4" FPT	4	24
2-07TK-54SF-2UNL	1-1/4" FPT Union	1" MPT X 3/4" FPT	3"	(2) 1/2" FPT	(2) 1/4" FPT	4	32

# BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

## STAINLESS STEEL UNION TANK TEES WITH PTFE (polytetrafluoroethylene) SEAL

**Boshart recommends -** Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.

- Heavy duty 304 Stainless Steel castings
- Ensures a watertight connection
- Provides a lead free option
- High corrosion resistance
- Replacement PTFE washers available for 1" P/N 07PT-TW10, for 1-1/4" P/N 07PT-TW12



07ST-8-2U

PART NO.	TANK CONNECTION	IN-LINE CONNECTION	CENTRE END LENGTH	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY	
						CTN	CASE
07ST-25S-2U	1" MPT	1" MPT X 3/4" FPT	4-1/2"	(2) 1/2" FPT	(2) 1/4" FPT	6	24
07ST-8-2U	1" MPT	1" MPT X 3/4" FPT	7-1/2"	(2) 1/2" FPT	(2) 1/4" FPT	6	24
07ST-25-2U	1" MPT	1" MPT X 3/4" FPT	10"	(2) 1/2" FPT	(2) 1/4" FPT	3	12
07ST-14X1-2U	1" MPT	1" MPT X 3/4" FPT	13"	(2) 1/2" FPT	(2) 1/4" FPT	3	12
07ST-13S-2U	1-1/4" MPT	1-1/4" MPT X 1" FPT	4-1/2"	(2) 3/4" FPT	(2) 1/4" FPT	4	16
07ST-13-2U	1-1/4" MPT	1-1/4" MPT X 1" FPT	13"	(2) 3/4" FPT	(2) 1/4" FPT	2	8

## NON-UNION STAINLESS STEEL TANK TEES

**Boshart recommends -** Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.

Heavy duty 304 investment cast stainless steel head casting c/w permanently installed Sch. 40 S.S. pipe nipple leg provide top quality construction.

- Permanent hard setting thread sealant ensures a watertight connection, and secures nipple in tank tee head, it will not un-thread if the tank tee needs to be removed to replace a defective pressure tank.
- Provides high corrosion resistance
- An excellent "Lead-Free" alternative



PART NO.	TANK CONNECTION	LINE CONNECTION	CENTRE END LENGTH	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY	
						CTN	CASE
07ST-25SFH-2	1" FPT*	1" MPT X 3/4" FPT	1-11/16"	(2) 1/2" FPT	(2) 1/4" FPT	5	40
07ST-25S-2	1" MPT	1" MPT X 3/4" FPT	4-1/2"	(2) 1/2" FPT	(2) 1/4" FPT	6	24
07ST-8-2	1" MPT	1" MPT X 3/4" FPT	7-1/2"	(2) 1/2" FPT	(2) 1/4" FPT	4	32
07ST-25-2	1" MPT	1" MPT X 3/4" FPT	10"	(2) 1/2" FPT	(2) 1/4" FPT	3	12
07ST-14X1-2	1" MPT	1" MPT X 3/4" FPT	13"	(2) 1/2" FPT	(2) 1/4" FPT	3	12
07ST-13SFH-2	1-1/4" FPT*	1-1/4" MPT X 1" FPT	1-7/8"	(2) 3/4" FPT	(2) 1/4" FPT	4	32
07ST-13S-2	1-1/4" MPT	1-1/4" MPT X 1" FPT	4-1/2"	(2) 3/4" FPT	(2) 1/4" FPT	4	24
07ST-13-2	1-1/4" MPT	1-1/4" MPT X 1" FPT	13"	(2) 3/4" FPT	(2) 1/4" FPT	2	8
07ST-16-2	1-1/4" MPT	1-1/4" MPT X 1" FPT	16"	(2) 3/4" FPT	(2) 1/4" FPT	3	12

\* The FPT tank connection is machined oversized to ensure the pipe nipple threads completely into the head casting leaving no exposed threads.

## GALVANIZED MALLEABLE IRON TANK TEES

- Heavy duty malleable iron castings
- Thick galvanized coating for corrosion resistance
- Compact and economical

07HC100G



PART NO.	TANK CONNECTION	IN-LINE CONNECTION	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY	
					CTN	CASE
07HC100G	1" FPT	1" FPT	(1) 3/4" FPT	(2) 1/4" FPT	1	30
07HC125G	1-1/4" FPT	1-1/4" FPT	(1) 3/4" FPT	(2) 1/4" FPT	1	20

## PVC TANK TEES

- PVC Material
- One-Piece Molded
- Complies with ASTM Socket & ANSI Threaded Standards
- Recommended working pressure 145 PSI



PART NO.	TANK CONNECTION	IN-LINE CONNECTION	CENTRE END LENGTH	DRAIN/RELIEF PORTS	ACCESSORY PORTS	QUANTITY	
						CTN	CASE
07-IC125	1-1/4" MPT X 1" F	1" MPT X 3/4" FPT	3-5/8"	(1) 3/4" FPT (1) 1/2" FPT	(2) 1/4" FPT		65
07PT-25-2	1" MPT	1" MPT X 3/4" Socket	11"	(2) 1/2" FPT	(2) 1/4" FPT	1	60

# BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

## STAINLESS STEEL CONSTANT PRESSURE MANIFOLD

**Boshart recommends** - Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.

- 1" FPT tank port makes this manifold functional with any tank on the market
- 1" FPT ports can be bushed down to match your tank and transducer
- MPT x FPT line connections on both ends for ease of installation
- Two 3/4" FPT ports accommodate a relief valve and a hose bibb
- One 1/4" FPT port accommodates a 2" or 2-1/2" dial 1/4" MPT center back mount gauge



PART NO.	TANK CONNECTIONS	IN-LINE CONNECTIONS	TOTAL LENGTH	TRANSDUCER PORT	DRAIN/RELIEF PORTS	PRESSURE GAUGE PORT	QUANTITY CTN	CASE
07M-125SS	1" FPT	1- 1/4" MPT x 1" FPT	11"	(1) 1"	(2) 3/4"	(1) 1/4"	4	24
07M-200SS	1" FPT	2" MPT x 1-1/2" FPT	13-3/4"	(1) 1"	(2) 3/4"	(1) 1/4"	1	12

## NO LEAD BRASS CONSTANT PRESSURE MANIFOLD

- Available with 3/4" or 1" FPT tank and transducer ports
- MPT x FPT line connections on both ends for ease of installation
- Two 3/4" FPT ports accommodate a relief valve and a hose bibb
- One 1/4" FPT port accommodates a 2" or 2-1/2" dial 1/4" MPT center back mount gauge



PART NO.	TANK CONNECTIONS	LINE CONNECTIONS	TOTAL LENGTH	TRANSDUCER PORT	DRAIN/RELIEF PORTS	PRESSURE GAUGE PORT	QUANTITY CTN	CASE
2-07M-125-10NL	1" FPT	1- 1/4" MPT x 1" FPT	13-5/8"	(1) 1"	(2) 3/4"	(1) 1/4"	1	16
2-07M-125NL	3/4" FPT	1- 1/4" MPT x 1" FPT	13-5/8"	(1) 3/4"	(2) 3/4"	(1) 1/4"	1	16

## MANIFOLD BRACKET

The bracket allows a manifold to be secured to the brackets with "U" bolts and a small pressure tank inserted to the manifold. This bracket is interchangeable to allow for two different mounting options. Brackets are steel with black powder coat finish and are supplied with lag screws, "U" bolts, nylon lock nuts and plastic end caps.

PART NO.	DESCRIPTION	QUANTITY CARTON
07M-125-MB	For 1-1/4" Manifold	20
07M-200-MB	For 2" Manifold	20



### SINGLE FLAT BAR MOUNTING BRACKET KIT

This NEW design allows the universal bracket to be installed anywhere a solid mounting structure exists. The 2" wide one piece zinc plated steel bracket is interchangeable to allow for two different mounting positions.

Each bracket comes complete with a hardware kit which includes:

- Three (3) 1/4" x 2" stainless steel hex head lag screws to mount on a single wall stud
- Three (3) 1/4" x 2" stainless steel nail in anchors to mount on a concrete wall
- Two (2) stainless steel U-Bolts
- Four (4) 1/4-20 UNC stainless steel nylon insert locking nuts



PART NO.	DESCRIPTION	QUANTITY CTN	CASE
07MB-125	2" wide x 7-3/4" x 11-3/4" with U-bolt for 1-1/4" Manifold	1	20
07MB-200	2" wide x 7-3/4" x 11-3/4" with U-bolt for 2" Manifold	1	20



POSITION 1



POSITION 2