

BOSHART INDUSTRIES

11-6
May 16/14

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

WTC SERIES BII WATERTITE WELL CAPS - FOR STEEL OR PVC WELL CASING

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Greater clearance for submersible pump cable
- Stainless steel hardware
- O-ring system ensures reliable watertight seal between well casing and retainer ring
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening 4 bolts
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
ALUMINUM							
WTC-A04	4"	4-1/2"	1" FPT	(2) 3/4"	3.00	16	44.80
WTC-A05	5"	5-9/16"	1" FPT	(2) 3/4"	3.25	12	49.10
WTC-A06	6"	6-5/8"	1" FPT	(2) 3/4"	4.00	12	54.62
WTC-A06-BLUE	6"	6-5/8"	1" FPT	(2) 3/4"	4.00	12	62.51
WTC-A06-12	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	4.00	12	56.24
WTC-A06-12-BLUE	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	4.00	12	77.59
WTC-PA06 *	6"	6 5/8"	1" FPT	(2) 3/4"	2.50	12	50.26
CAST IRON - Durable Blue Powder Coat Paint							
WTC-C06	6"	6-5/8"	1" FPT	(2) 3/4"	9.5	6	64.18
WTC-C06-12	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	9.5	6	64.64



WTC Series



WTC-A06-BLUE
(Durable Powder Coat Paint)



*WTC-PA06
(PVC cover c/w Alum. lower ring for steel casing)



WTC-C06
(Durable Powder Coat Paint)

8, 10 and 12" available in locking style only, see WTCL series, Page 11-8

WTC-G SERIES BII WATERTITE CAPS FOR PVC WELL CASING

- Same design as the above WTC Series but with exception that the lower ring is plastic which can be solvent welded directly to PVC well casing
- Durable UV stabilized, high impact ABS



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTC-G-P0625-06 *	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	1.93	12	35.46
WTC-G-P0625	6-1/4"	6.90"	1" FPT	(2) 3/4"	1.75	12	32.76
WTC-G-AP0625-06 *	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	2.93	12	53.41
WTC-G-AP0625-06-B	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	2.93	12	48.10
WTC-G-AP0625	6-1/4"	6.90"	1" FPT	(2) 3/4"	2.75	12	50.26

* New models of well caps for 6-5/8" well casing are now available. These caps are the 6-1/4" well caps for 6.9" O.D. casing shipped with a Part No. WCCA-G0625-G06 6.9" X 6-5/8" well cap casing adapter included. The reducing adapter is not glued into the well cap so that the end user has the flexibility to use the cap for either a 6.9" O.D. or a 6-5/8" O.D. casing. This also gives the option to reduce inventories for those customers whom have both casing sizes in their territory, ensuring they never end up at a job site with the wrong size well cap.



WTC-G-P0625
ABS top with
ABS glue-on
lower ring



WTC-G-AP0625
Aluminum top with
ABS glue-on lower
ring



WTC-G-P0625-06
consists of
WTC-G-P0625 well cap
plus a
WCCA-G0625-G06 ring
WTC-G-AP0625

WELL CAP CASING ADAPTER

PART NO.	SIZE	UNIT WGT-lbs	QTY CASE	LIST PRICE-A
WCCA-G0625-G06	6.9" X 6-5/8"	0.175	1	2.89

Well cap casing adapters (reducer rings) can be purchased separately if desired. If an account would prefer the option of stocking the 6-1/4" well caps for 6.9" O.D. well casing and selling the rings as a separate component. The rings are individually bagged and include installation information.



WCCA-G0625-G06 ring
glued on a 6-5/8"
casing