



## BIBD2502, 2-Sided Two Cond. Clear Ins. MultiTap

By Burndy  
Catalog # [BIBD2502](#)

#10 AWG - 250 kcmil, 2 Ports, Double-sided Entry, Al/Cu Rated, Clear Plastisol allows visual confirmation conductor is properly inserted



### Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

|                                         |              |
|-----------------------------------------|--------------|
| Certification - UL Recognized           | No           |
| Buy American Compliant                  | No           |
| Certification - cULus                   | No           |
| EU RoHS Indicator                       | Yes          |
| Industry Standard(s)                    | UL 486A-486B |
| Certification - ETL                     | No           |
| Standards - Industry Standards Met      | UL 486A-486B |
| Standards - RoHS Compliance Status      | CM           |
| Certification - UL Listed Direct Burial | No           |
| UL Listed                               | Yes          |
| Certification - CSA Approved            | Yes          |

### Conductor

|                               |                                                                                                                                                                                                                                                 |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor - AL Str Size       | <ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> </ul> |
| Conductor - AL Str Size Range | 8 AWG-250 kcmil                                                                                                                                                                                                                                 |
| Conductor - Copper Str Size   | <ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> </ul>                                                                                                                                                                     |

- 8 AWG
- 7 AWG
- 6 AWG
- 5 AWG
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil

|                                   |                                                                                            |
|-----------------------------------|--------------------------------------------------------------------------------------------|
| Conductor Size                    | 10 AWG-250 KCMIL                                                                           |
| Conductor Type                    | <ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul> |
| Conductor - Copper Str Size Range | 10 AWG - 250 kcmil                                                                         |

### Configuration

|                                       |           |
|---------------------------------------|-----------|
| Physical Attribute - Number of Screws | 2         |
| Number Of Ports                       | 2         |
| Connector Type                        | Multi Tap |

### Current

|                   |       |
|-------------------|-------|
| Voltage - Maximum | 600 V |
|-------------------|-------|

### Dimensions

|                                 |            |
|---------------------------------|------------|
| Package Height                  | 0.000 in   |
| Dimension - Height mm           | 54.1 mm    |
| Dimension - Height inch         | 2.13 in    |
| Dimension - Height fraction     | 2.125 in   |
| Package Weight                  | 0.000 lb.  |
| Package Length                  | 0.000 in   |
| Package Width                   | 0.000 in   |
| Dimension - L Length Overall mm | 52 mm      |
| Dimension - Width fraction      | 2-16/25 in |
| Dimension - Width mm            | 67 mm      |
| Dimension - Width inch          | 2.64 in    |
| Dimension - Length Overall inch | 2.03 in    |

### General

|                                 |                  |
|---------------------------------|------------------|
| Insulation Type                 | Plastisol        |
| Trade Name                      | UNITAP™          |
| Material - Hardware             | Aluminum         |
| Insulation                      | Y                |
| Physical Attribute - Screw Type | Allen            |
| Plated                          | N                |
| Sub Brand                       | UNITAP           |
| UPC                             | 781810224052     |
| Type                            | BIBD, Multi-Port |
| Hex Key                         | 5/16             |
| Material                        | Aluminum         |
| Plating Type                    | Unplated         |
| UPC 12 Digit                    | 781810224052     |

UPC 14 Digit GTIN 00781810224052

### Logistics

|                       |      |
|-----------------------|------|
| Minimum Pack Quantity | 1    |
| Pallet Quantity       | 2304 |
| Carton Quantity       | 24   |

### Operational

|                    |     |
|--------------------|-----|
| Temperature Rating | 194 |
|--------------------|-----|

### Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)



A Hubbell brand