

## BIBD3502, 2-Sided, 2-Cond. Clear Ins. MultiTap

By Burndy  
Catalog # [BIBD3502](#)

#10 AWG - 350 kcmil, 2 Port, Double-sided Entry, Al/Cu Rated, Clear Plastisol allows visual confirmation conductor is properly inserted



### Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

### Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> <li>• 266 kcmil</li> </ul>
-------------------------	--

	<ul style="list-style-type: none"> <li>• 300 kcmil</li> <li>• 336 kcmil</li> <li>• 350 kcmil</li> </ul>
Conductor - AL Str Size Range	8 AWG-350 kcmil
Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> <li>• 300 kcmil</li> <li>• 350 kcmil</li> </ul>
Conductor Size	10 AWG-350 KCMIL
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>
Conductor - Copper Str Size Range	10 AWG - 350 kcmil

### Configuration

Physical Attribute - Number of Screws	2
Number Of Ports	2
Connector Type	Multi Tap

### Current

Voltage - Maximum	600 V
-------------------	-------

### Dimensions

Package Height	0.000 in
Dimension - Height mm	63.5 mm
Dimension - Height inch	2.50 in
Dimension - Height fraction	2.5 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in

Dimension - L Length Overall mm 56 mm  
Dimension - Width mm 76 mm  
Dimension - Width inch 3.00 in  
Dimension - Length Overall inch 2.22 in

### General

Insulation Type Plastisol  
Trade Name UNITAP™  
Material - Hardware Aluminum  
Insulation Y  
Physical Attribute - Screw Type Allen  
Plated N  
Sub Brand UNITAP  
UPC 781810224083  
Type BIBD, Multi-Port

Hex Key 5/16  
Material Aluminum  
Plating Type Unplated  
UPC 12 Digit 781810224083  
UPC 14 Digit GTIN 00781810224083

### Logistics

Minimum Pack Quantity 1  
Pallet Quantity 1728  
Carton Quantity 24

### Operational

Temperature Rating 194

### Product Assets

[Catalog \[English\]](#)  
[Catalog \[English\]](#)



A Hubbell brand