



## BIBS2506, 6-Cond. Clear Ins. Multi-Tap, Al/Cu Rated

By Burndy  
Catalog # [BIBS2506](#)

#10 AWG - 250 kcmil, 6 Ports, Single-sided Entry, Al/Cu Rated,  
Clear Plastics allows visual confirmation conductor is properly  
inserted



## Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

## Application

For Indoor Use Only, Copper Or Stranded Aluminum

## Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

## Conductor

Conductor - AL Str Size Range	10 AWG - 250 kcmil
Conductor Size	10 AWG-250 KCMIL
Conductor Type	<ul style="list-style-type: none"><li>• AL C Str-Size</li><li>• CU C Str-Size</li></ul>
Conductor - Copper Str Size Range	10 AWG - 250 kcmil

## Configuration

Physical Attribute - Number of Screws	6
Number Of Ports	6
Connector Type	Multi Tap

## Current

Voltage - Maximum	600 V
-------------------	-------

## Dimensions

Package Height	0.000 in
Dimension - Height mm	54 mm
Dimension - Height inch	2.13 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	147 mm
Dimension - Width mm	53 mm
Dimension - Width inch	2.07 in
Dimension - Length Overall inch	5.78 in

## General

Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Physical Attribute - Screw Type	Allen
Plated	N
Sub Brand	UNITAP
UPC	781810224045
Type	BIBS, Multi-Port
Hex Key	5/16
Material	Aluminum
Plating Type	Unplated
UPC 12 Digit	781810224045
UPC 14 Digit GTIN	00781810224045

## Logistics

Minimum Pack Quantity	1
Pallet Quantity	1536
Carton Quantity	24

## Operational

Temperature Rating	194
--------------------	-----

## Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)



A Hubbell brand