

## BIBS44, 4-Cond., 1-Side, Clear Ins. Multi-Tap

By Burndy  
Catalog # BIBS44

Aluminum Multiple Tap Connector, Clear Insulated, 4 Port, 1 Sided Entry, 14-4 AWG, Al/Cu Rated



### Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

### Conductor

Conductor - AL Str Size Range	14 AWG - 4 AWG
Conductor Size	14-4 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>
Conductor - Copper Str Size Range	14 AWG - 4 AWG

### Configuration

Physical Attribute - Number of Screws	4
Number Of Ports	4
Connector Type	Multi Tap

### Current

Operating Voltage	600 V
Voltage - Maximum	600 V

### Dimensions

Package Height	0.000 in
Dimension - Height mm	31.8 mm
Dimension - Height inch	1.25 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	50 mm
Dimension - Screw Size inch	1/4
Dimension - Width mm	32 mm
Dimension - Width inch	1.25 in
Dimension - Length Overall inch	1.95 in

### General

Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Physical Attribute - Screw Type	Allen
Plated	N
Sub Brand	UNITAP
UPC	781810134122
Type	BIBS, Multi-Port
Hex Key	1/8
Material	Aluminum
Plating Type	Unplated
UPC 12 Digit	781810134122
UPC 14 Digit GTIN	00781810134122

### Logistics

Minimum Pack Quantity	1
Pallet Quantity	8000
Carton Quantity	250

### Operational

Temperature Rating	90° C
--------------------	-------

## Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)

---



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved  
BRDY-BIBS44-SPEC-EN | REV 5/2026