

## BIT350, 1-Side, 2-Cond. Clear Ins., MultiTap

By Burndy  
Catalog # BIT350

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 10 AWG-350 kcmil, Al/Cu Rated



### Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

|   |              |
|---|--------------|
| Certification - UL Recognized           | No           |
| Buy American Compliant                  | No           |
| Certification - cULus                   | No           |
| EU RoHS Indicator                       | Yes          |
| Industry Standard(s)                    | UL 486A-486B |
| Certification - ETL                     | No           |
| Standards - Industry Standards Met      | UL 486A-486B |
| Standards - RoHS Compliance Status      | CM           |
| Certification - UL Listed Direct Burial | No           |
| UL Listed                               | Yes          |
| Certification - CSA Approved            | Yes          |

### Conductor

|                               |   |
|-------------------------------|---|
| Conductor - AL Str Size       | <ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> </ul> |
| Conductor - AL Str Size Range | 10 AWG - 350 kcmil  |
| Conductor - Copper Str Size   | <ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> </ul>  |

- 3 AWG
- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil

|                                   |  |
|-----------------------------------|--|
| Conductor Size                    | 10 AWG-350 KCMIL   |
| Conductor Type                    | <ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul> |
| Conductor - Copper Str Size Range | 10 AWG - 350 kcmil   |

### Configuration

|                                       |           |
|---------------------------------------|-----------|
| Physical Attribute - Number of Screws | 2         |
| Number Of Ports                       | 2         |
| Connector Type                        | Multi Tap |

### Current

|                   |       |
|-------------------|-------|
| Operating Voltage | 600 V |
| Voltage - Maximum | 600 V |

### Dimensions

|                                 |           |
|---------------------------------|-----------|
| Package Height                  | 0.000 in  |
| Dimension - Height mm           | 64 mm     |
| Dimension - Height inch         | 2.5 in    |
| Dimension - Height fraction     | 2.5 in    |
| Package Weight                  | 0.000 lb. |
| Package Length                  | 0.000 in  |
| Package Width                   | 0.000 in  |
| Dimension - L Length Overall mm | 56 mm     |
| Dimension - Width fraction      | 2-8/25 in |
| Dimension - Width mm            | 59 mm     |
| Dimension - Width inch          | 2.32 in   |
| Dimension - Length Overall inch | 2.22 in   |

### General

|                 |           |
|-----------------|-----------|
| Insulation Type | Plastisol |
| Trade Name      | UNITAP™   |

|                                 |                |
|---------------------------------|----------------|
| Material - Hardware             | Aluminum       |
| Insulation                      | Y              |
| Physical Attribute - Screw Type | Allen          |
| Plated                          | N              |
| Sub Brand                       | UNITAP         |
| UPC                             | 781810133538   |
| Type                            | BIT            |
| Hex Key                         | 5/16 in        |
| Material                        | Aluminum       |
| Plating Type                    | Unplated       |
| UPC 12 Digit                    | 781810133538   |
| UPC 14 Digit GTIN               | 00781810133538 |

### Logistics

|                       |      |
|-----------------------|------|
| Minimum Pack Quantity | 1    |
| Pallet Quantity       | 2160 |
| Carton Quantity       | 60   |

### Operational

|                    |       |
|--------------------|-------|
| Temperature Rating | 90 °C |
|--------------------|-------|

### Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)



A Hubbell brand