

BIT600, 1-Side, 2-Cond. Clear Ins., MultiTap

By Burndy
Catalog # BIT600

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated



Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

| | |
|---|----------------------|
| Buy American Compliant | Contact Manufacturer |
| EU RoHS Indicator | Yes |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance | CM |
| Status | |
| Certification - UL Listed Direct Burial | No |
| UL Listed | Yes |
| Certification - CSA Approved | Yes |

Conductor

| | |
|-----------------------------------|--|
| Conductor - AL Str Size Range | 4 AWG - 600 kcmil |
| Conductor Size | 4 AWG-600 KCMIL |
| Conductor Type | <ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size |
| Conductor - Copper Str Size Range | 4 AWG - 600 kcmil |

Configuration

| | |
|---------------------------------------|-----------|
| Physical Attribute - Number of Screws | 2 |
| Number Of Ports | 2 |
| Connector Type | Multi Tap |

Current

| | |
|-------------------|-------|
| Operating Voltage | 600 V |
| Voltage - Maximum | 600 V |

Dimensions

| | |
|---------------------------------|------------|
| Package Height | 0.000 in |
| Dimension - Height mm | 69.9 mm |
| Dimension - Height inch | 2.75 in |
| Package Weight | 0.000 lb. |
| Package Length | 0.000 in |
| Package Width | 0.000 in |
| Dimension - L Length Overall mm | 69 mm |
| Dimension - Width fraction | 2-19/50 in |
| Dimension - Width mm | 60 mm |
| Dimension - Width inch | 2.38 in |
| Dimension - Length Overall inch | 2.72 in |

General

| | |
|---------------------------------|----------------|
| Insulation Type | Plastisol |
| Trade Name | UNITAP™ |
| Material - Hardware | Aluminum |
| Insulation | Y |
| Physical Attribute - Screw Type | Allen |
| Plated | N |
| Sub Brand | UNITAP |
| UPC | 781810225257 |
| Type | BIT |
| Hex Key | 3/16 |
| Material | Aluminum |
| Plating Type | Unplated |
| UPC 12 Digit | 781810225257 |
| UPC 14 Digit GTIN | 00781810225257 |

Logistics

| | |
|-----------------------|------|
| Minimum Pack Quantity | 1 |
| Pallet Quantity | 1400 |
| Carton Quantity | 50 |

Operational

| | |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)