




## GP6429, Mech Grounding Conn, 2 Cables to Rod or Pipe

By Burndy  
Catalog # [GP6429](#)

2 Cables to Rod or Pipe, 2/0 AWG Sol-250 kcmil, 3/8" Pipe, 5/8"  
to 3/4" Rod, 3/8" Stud



## Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

## Application

For Joining A Range Of Parallel Copper Cables Perpendicular To Rod, Pipe Or Column, Direct Burial In Earth Or Concrete

## Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

## Conductor

Conductor - Rod Size Range	5/8 in-3/4 in
Conductor - Copper Str Size	<ul style="list-style-type: none"><li>• 1/0</li><li>• 2/0</li><li>• 3/0</li><li>• 4/0</li><li>• 250</li></ul>
Conductor - Rod Size	<ul style="list-style-type: none"><li>• 5/8 in</li><li>• 3/4 in</li></ul>
Conductor - Copper Solid Size	<ul style="list-style-type: none"><li>• 2/0</li><li>• 3/0</li><li>• 4/0</li></ul>
Conductor - Copper Solid Size Range	2/0-4/0
Conductor - Copper Str Size Range	1/0-250
Conductor - Copper Str Size B Range	0.375

Conductor - Copper Tube Std Size Range	5/8-3/4
Conductor - Copper Tube Std Size	<ul style="list-style-type: none"><li>• 5/8</li><li>• 3/4</li></ul>

## Dimensions

Package Height	0.000 in
Dimension - Height mm	73.2 mm
Dimension - Height inch	2.88 in
Dimension - Height fraction	2-7/8 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	52 mm
Dimension - Width fraction	2-1/8 in
Dimension - Width mm	54 mm
Dimension - Width inch	2.12 in
Dimension - B Length inch	1.75 in
Dimension - Length Overall inch	2.06 in

## Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

## General

Material Type - Screw Plated	DURIUM™ Silicon Bronze N
Sub Brand	MECHANICAL CONNECTOR
UPC	781810260555
Type	GP
U Bolt Type	242
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810260555
UPC 14 Digit GTIN	00781810260555

## Logistics

Minimum Pack Quantity	1
Pallet Quantity	1
Carton Quantity	12

## Product Assets

[Catalog \[English\]](#)



A Hubbell brand