

K21A36U2, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy
Catalog # [K21A36U2](#)

Aluminum Universal Terminal, 3 Conductor, 2 Holes, 2 AWG (Str)-600 kcmil, 3/8" Stud, 1.38" Spacing



Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil
-------------------------	--

Conductor - AL Str Size Range	2 Str. - 600 Kcmil
Conductor - Copper Str Size	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil • 550 kcmil • 600 kcmil
Number Of Conductors	3
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	2 Str. - 600 Kcmil

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	2
Connector Type	Stacked

Dimensions

Dimension - Pad Width inch	2.49 in
Package Height	0.000 in
Dimension - Height mm	77 mm
Dimension - Height inch	3.03 in
Dimension - Height fraction	3 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	125 mm
Dimension - Width fraction	2-1/2 in
Dimension - Hole Size mm	10 mm
Dimension - Hole Size inch	0.41 in
Dimension - Stud Size inch	3/8 in
Dimension - Bolt Hole Size inch	0.38 in
Dimension - Bolt Size fraction	3/8

Dimension - Width mm 64 mm
Dimension - Width inch 2.5 in
Dimension - D inch 2.31 in
Dimension - N inch 0.38 in
Dimension - Length Overall
inch 4.91 in

Force Related

Installation Torque 375 LBS/in
Recommended in-lb

General

Material - Hardware Aluminum
Physical Attribute - Screw Type Allen
Plated Y
Sub Brand UNIVERSAL TERM
UPC 781810370322

Type Bolted Lugs & Terminals
Material Aluminum
Plating Type Tin plated
UPC 12 Digit 781810370322
UPC 14 Digit GTIN 00781810370322

Logistics

Minimum Pack Quantity 1
Pallet Quantity 576
Carton Quantity 18

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)



A Hubbell brand