

K2A36U2N, AL Universal Terminal, 2-Conductor, 2-Hole

By Burndy

Catalog # [K2A36U2N](#)

2-Conductor, 2-Hole, 1/2" Stud, 1.75" Spacing, #2 AWG-600 kcmil, Tin Plated



Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy America Compliant (All status valid till December 2026) • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil
-------------------------	---

- 500 kcmil
- 550 kcmil
- 556 kcmil
- 600 kcmil

Conductor - AL Str Size Range 2 Str. - 600 Kcmil
 Conductor - Copper Str Size

- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil
- 400 kcmil
- 450 kcmil
- 500 kcmil
- 550 kcmil
- 600 kcmil

Conductor Size 2 AWG-600 KCMIL
 Number Of Conductors 2
 Conductor Type

- AL C Str-Size
- CU C Str-Size

 Conductor - Copper Str Size Range 2 Str. - 600 Kcmil

Configuration

Physical Attribute - Number of Holes 2
 Connector Type Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	2.42 in
Package Height	2.100 in
Dimension - Height mm	35.3 mm
Dimension - Height inch	1.39 in
Dimension - Height fraction	1.4 in
Package Weight	2.030 lb.
Package Length	6.400 in
Package Width	6.000 in
Dimension - L Length Overall mm	119 mm
Dimension - Width fraction	2-41/100 in
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Screw Size inch	3/8

Dimension - Stud Size inch 1/2 in
Dimension - Bolt Hole Size inch 0.50 in
Dimension - Bolt Size fraction 1/2
Dimension - Width mm 61 mm
Dimension - Width inch 2.42 in
Dimension - D inch 3.22 in
Dimension - N inch 0.63 in
Dimension - Length Overall
inch 4.69 in

Force Related

Installation Torque 375 LBS/in
Recommended in-lb

General

Material - Hardware Aluminum
Physical Attribute - Screw Type Slot
Plated N
Sub Brand UNIVERSAL TERM

UPC 781810600351
Type Bolted Lugs & Terminals
Material Aluminum
Plating Type Tin plated
UPC 12 Digit 781810600351
Hardware Type 3/8 UNC Slotted Set Screw
UPC 14 Digit GTIN 00781810600351

Logistics

Minimum Pack Quantity 1
Pallet Quantity 1728
Carton Quantity 54

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)



A Hubbell brand