

K3A25U2, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy
Catalog # [K3A25U2](#)



3-Conductor, #14-1/0 AWG, 2-Hole, 3/8" Stud, 1" Spacing, Dual Rated, Tin Plated

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG
Conductor - AL Str Size Range	14 Str.-1/0 AWG
Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG

Conductor Size	2 AWG
Number Of Conductors	1 AWG
Conductor Type	1/0
Conductor - Copper Str Size Range	14-1/0 AWG
	3
	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size
	14 Str.-1/0 AWG

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	2
Number Of Ports	3
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	2.02 in
Package Height	0.000 in
Dimension - Height mm	22.4 mm
Dimension - Hole Size fraction	7/16
Dimension - Height inch	0.88 in
Dimension - Height fraction	7/8 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	56 mm
Dimension - Width fraction	1-47/50 in
Dimension - Hole Size mm	11 mm
Dimension - Hole Size inch	0.45 in
Dimension - Stud Size inch	3/8 in
Dimension - Bolt Hole Size inch	0.44 in
Dimension - Bolt Size fraction	3/8
Dimension - Width mm	49 mm
Dimension - Width inch	1.64 in
Dimension - D inch	2.09 in
Dimension - N inch	0.34 in
Dimension - Length Overall inch	2.19 in

Force Related

Installation Torque Recommended in-lb	50 LBS/in
---------------------------------------	-----------

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	Y
Sub Brand	UNIVERSAL TERM
UPC	781810370537
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin plated
UPC 12 Digit	781810370537
UPC 14 Digit GTIN	00781810370537

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1
Carton Quantity	216

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand