



K3A36U2N, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy

Catalog # [K3A36U2N](#)

3-Conductor, 2-Hole, 1/2" Stud, 1.75" Spacing, #2 AWG-600 kcmil, Tin Plated



Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy America Compliant (All status valid till December 2026) • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil
-------------------------	---

- 500 kcmil
- 550 kcmil
- 556 kcmil
- 600 kcmil

Conductor - AL Str Size Range 2 Str. - 600 Kcmil
 Conductor - Copper Str Size

- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil
- 400 kcmil
- 450 kcmil
- 500 kcmil
- 550 kcmil
- 600 kcmil

Conductor Size 2 AWG-600 KCMIL
 Number Of Conductors 3
 Conductor Type

- AL C Str-Size
- CU C Str-Size

 Conductor - Copper Str Size Range 2 Str. - 600 Kcmil

Configuration

Physical Attribute - Number of Screws 3
 Physical Attribute - Number of Holes 2
 Connector Type Parallel Set-Screw

Dimensions

Dimension - Pad Width inch 3.64 in
 Package Height 3.450 in
 Dimension - Height mm 39.6 mm
 Dimension - Hole Size fraction 9/16
 Dimension - Height inch 1.56 in
 Dimension - Height fraction 1.5555555555555556 in
 Package Weight 2.220 lb.
 Package Length 5.450 in
 Package Width 4.750 in
 Dimension - L Length Overall mm 119.12 mm
 Dimension - Width fraction 3-63/100 in

Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	92 mm
Dimension - Width inch	3.64 in
Dimension - D inch	3.22 in
Dimension - N inch	0.63 in
Dimension - Length Overall inch	4.69 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot

Plated	Y
Sub Brand	UNIVERSAL TERM
UPC	781810601204
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin plated
UPC 12 Digit	781810601204
UPC 14 Digit GTIN	00781810601204

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1152
Carton Quantity	36

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand