


## KC22, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy  
Catalog # [KC22](#)

Mechanical SERVIT POST™ Connector, Cable to Flat



### Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

### Application

For Direct Burial Applications And Used To Ground One Or Two Cables To Steel Structures, Fence Posts, Transformers, Also Used To Tap One Or Two Cables From Bus Bar

### Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

### Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul>
Conductor - Copper Solid Size	<ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul>

	• 2 AWG
Conductor - Copper Solid Size Range	2 AWG-10 AWG
Physical Attribute - Number of Conductors Accommodated Total	1
Conductor - Copper Str Size Range	3 AWG-10 AWG

### Dimensions

Package Height	0.000 in
Dimension - Height mm	25.4 mm
Dimension - Height inch	1.00 in
Dimension - Height fraction	1
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - P inch	0.26 in
Dimension - L Length Overall mm	41.1 mm
Dimension - Nut Width inch	0.75 in
Dimension - Threads per inch	16
Dimension - Bolt Size fraction	3/8
Dimension - Body Width inch	0.62 in
Dimension - B Length fraction	15/32 in
Dimension - Width inch	25 mm
Dimension - B Length inch	0.46 in
Dimension - D inch	0.63 in
Dimension - Length Overall inch	1.62 in

### Force Related

Stud Installation Torque inch pounds	280 LBS/in
--------------------------------------	------------

### General

Trade Name	SERVIT POST™
Plated	N
Sub Brand	SERVIT POST
UPC	781810254905
Type	KC and K2C Series
Material	Bronze, Leaded, Commercial
Plating Type	Leaded Bronze Alloy
UPC 12 Digit	781810254905
UPC 14 Digit GTIN	00781810254905

**Logistics**

Minimum Pack Quantity 1  
Pallet Quantity 14850

Carton Quantity 50

**Product Assets**

[Catalog \[English\]](#)



A Hubbell brand