




KS25, Split Bolt Connector, Run/Tap: #4 AWG-1/0 AWG Str

By Burndy
Catalog # [KS25](#)

Copper Split Bolt, Cu: 4 AWG-1/0 AWG (Str) (Run & Tap)



Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	RUS
Buy America(n) Qualified	• Buy America Compliant (All status valid till December 2025) • Buy American Act Compliant (All status valid till December 2025) • BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Solid Run	2/0 AWG
Conductor - Copper Solid Run Range	4 AWG-1/0
Conductor - Copper Solid Tap	2/0 AWG
Conductor - Copper Solid Tap Range	14 AWG-1/0
Conductor - Copper Str Run	• 4 AWG • 3 AWG • 2 AWG • 1 AWG

Conductor - Copper Str Run Range	• 1/0 4 STR - 1/0 STR
Conductor - Copper Str Tap	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 4 STR - 1/0 STR
Conductor - Copper Str Tap Range	4 STR - 1/0 STR
Conductor Type	• CU C Solid-Run • CU C Str-Run • CU Weld C Solid-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Solid-Tap • CU Weld C Str-Tap • CU C Solid-Tap
Conductor - CopperWeld Solid Run	2/0
Conductor - CopperWeld Solid Run Range	2/0
Conductor - CopperWeld Solid Tap	2/0
Conductor - CopperWeld Solid Tap Range	2/0
Conductor - CopperWeld Str Run	• 4 D AWG • 4 N AWG • 4 P AWG • 3 A AWG • 3 J AWG • 3 K AWG • 3 N AWG • 3 P AWG • 2 A AWG
Conductor - CopperWeld Str Run Range	4 D AWG-2 A AWG
Conductor - CopperWeld Str Tap	• 5 D AWG • 5 P AWG

	• 4 A AWG • 4 D AWG • 4 N AWG • 4 P AWG • 3 A AWG • 3 J AWG • 3 K AWG • 3 N AWG • 3 P AWG • 2 A AWG
Conductor - CopperWeld Str Tap Range	5 D AWG-2 A AWG

Configuration

Connector Type	Split Bolt
----------------	------------

Dimensions

Dimension - L Length Overall mm	45 mm
Width	0.73 in
Dimension - Width fraction	73/100 in
Dimension - Width inch	0.73 in
Dimension - Width mm	19 mm
Dimension - B Length fraction	83/100 in
Dimension - B Length inch	.83 in

Dimension - Length Overall inch	1.77
Dimension - Cross Flats inch	0.94 in

Force Related

Installation Torque Recommended in-lb	385 in
---------------------------------------	--------

General

Trade Name	SERVIT®
Sub Brand	SERVIT
Plated	N
Type	KS, Compact
UPC 12 Digit	781810013106
UPC 14 Digit GTIN	00781810013106
Material	Copper
Plating Type	Unplated
UPC	781810013106

Logistics

Minimum Pack Quantity	50
Carton Quantity	50
Pallet Quantity	11600

Product Assets

[Catalog \[English\]](#)