



## KSU29, Split Bolt Connector with Spacer, Tin Plated

By Burndy  
Catalog # [KSU29](#)

Tin-plated, high strength copper alloy SERVIT™ with spacer



### Features

- Tin-plated, high strength copper alloy with spacer
- Spacer separates dissimilar conductors and provides long contact length preventing high pressure point contacts between run and tap conductors

### Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005, And Steel

### Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes

### Conductor

Conductor - Copper Str Run Range	1 AWG - 250 KCMIL
Conductor - Copper Str Tap Range	8 AWG - 250 KCMIL
Conductor - ACSR Str Run Range	2/0 AWG - 4/0 AWG

Conductor - ACSR Str Tap Range	6 AWG - 4/0 AWG
Conductor - AL Str Run Range	1 AWG - 250 KCMIL
Conductor - AL Str Tap Range	8 AWG - 250 KCMIL

### Dimensions

Dimension - Length Overall	2.66 inch
Width	1.22 in

### General

Sub Brand	UNIVERSAL SERVIT
Trade Name	SERVIT®
Plated	Y
Type	KSU, Universal
Material	Copper
Plating Type	Tin Plated
UPC	781810036853

### Logistics

Minimum Pack Quantity	1
Carton Quantity	1
Pallet Quantity	1

### Product Assets

[Catalog \[English\]](#)