



UGS350ULDB, In-Line Splice/Reducer, Direct Burial Rated

By Burndy
Catalog # [UGS350ULDB](#)

12 AWG-350 kcmil Al/Cu, Dual Rated, UL Listed, CSA Certified, Direct Burial



Features

- EPDM rubber covered 6061-T6 aluminum connector dual rated (AL9CU) for copper or aluminum
- UL Listed, CSA Certified for Direct Burial
- Broad range taking capability with low installation cost

Application

For Direct Burial

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL486D
Certification - ETL	No
Standards - Industry Standards Met	UL486D
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	8 AWG-350 kcmil
Conductor - Copper Str Size	<ul style="list-style-type: none"> • 12 AWG • 10 AWG • 9 AWG

- 8 AWG
- 7 AWG
- 6 AWG
- 5 AWG
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil

Conductor Size	12 AWG-350 KCMIL
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	12 AWG-350 kcmil

Configuration

Connector Type	In-Line
----------------	---------

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Package Height	0.000 in
Dimension - Height mm	71.4 mm
Dimension - Height inch	2.81 in
Dimension - Height fraction	2.8333333333333335 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	216 mm
Dimension - Strip Length inch Length	1 3/8 8.5 in
Height	2.83 in
Dimension - Length Overall inch	8.50 in
Hex Size	5/16

Force Related

Installation Torque 350 LBS/in
Recommended in-lb

UPC 14 Digit GTIN 00781810343807

General

Insulation Type Rubber
Trade Name UNITAP™
Insulation Y
Physical Attribute - Screw Type Slot
Plated N
Sub Brand SPLICE KIT
UPC 781810343807
Type In-Line, Underground
Material Brass
Plating Type Unplated

Logistics

Minimum Pack Quantity 1
Pallet Quantity 1344
Carton Quantity 24

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)



A Hubbell brand