



YAV2CL2NT14FX, Cu Compression, 2-Hole, 1/4" Stud, 5/8" Spacing, Narrow Tongue, Standard Barrel, 2 Flex

By Burndy

Catalog # [YAV2CL2NT14FX](#)

2 Flex G,H,I,K,M,DLO, 2 AWG, CU, 2 Hole, 1/4 Stud, 5/8 IN Spacing, Standard Barrel, Inspection Window, Narrow Tongue

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2 AWG
Conductor - Copper Str Size	"2 AWG"
Conductor - Copper Flex I Size Range	2 AWG
Conductor - Copper Flex K Size	"2 AWG"
Conductor - Copper Flex K Size Range	2 AWG
Conductor - Copper Flex M Size	"2 AWG"
Conductor - Copper Solid Size	2 AWG
Conductor - Copper Str Compact Size	"2 AWG"
Conductor - Copper DLO Size	2 AWG
Conductor - Copper DLO Size Range	2 AWG
Conductor - Copper Flex G Size	"2 AWG"
Conductor - Copper Str Navy Size	60
Conductor - Copper Flex G Size Range	2 AWG



Conductor - Copper Str Navy Size Range	60 (37) Navy
Conductor - Copper Flex H Size	"2 AWG"
Conductor Size	2 AWG
Conductor - Copper Str Size Range	2 AWG
Conductor - Copper Flex H Size Range	2 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"2 AWG"
Conductor - CopperWeld Str Size	• 2 A AWG • 2 F AWG • 2 G AWG • 2 J AWG • 2 K AWG • 2 N AWG • 2 P AWG

Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.46 in
Dimension - L Length Overall mm	57 mm
Dimension - Pad Width inch	0.48 in
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	11/16
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4
Dimension - B Length fraction	5/8 in
Dimension - B Length inch	0.63 in
Dimension - Z inch	0.34 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in

Dimension - Bolt Size fraction	1/4	UPC 14 Digit GTIN	00781810274217
Dimension - Bolt Size inch	0.25	Material	COPPER
Dimension - Length Overall inch	2.26 in	Plating Type	Tin - Electro Plated
Dimension - N inch	0.31 in	Finish Type	Tin-Plated
		UPC	781810274217
General		Logistics	
Die Index	10	Minimum Pack Quantity	1
Trade Name	HYLUG™	Carton Quantity	50
Sub Brand	HYLUG		
Color Code	Brown	Product Assets	
Plated	Y	Catalog [English]	
Feature - Barrel Type	Standard	Installation Manual [English]	
Feature - Barrel Style	Chamfered	Installation Manual [English]	
Type	YAV-L-NTFX, Standard Barrel		
	Narrow Tongue		

