


# GCALEFFI Hydronic Solutions



Heating & Cooling Components for today's modern hydronic systems





## **FUNCTIONS AND FEATURES**

- Hydraulic separation: creates low pressure loss zone, making connected primary and secondary circuits hydraulically independent; flow in one circuit does not interfere with flow in the other.
- Microbubble air separation: the widening of the cross section decreases the flow velocity and the internal element facilitate the release of mircobubbles.
- Microparticle dirt separation: The internal element separates and collects all the particles in the dirt collection chamber. Collected particles are discharged with the drain valve, even with the system operating.
- Magnetic separation of ferrous impuritites: the powerful, external rare earth magnet captures ferrous impurities. Removing the magnetic ring allows for discharging through drain valve even with system operating.

#### PRODUCT RANGE - 5495 SERIES


1
0
0
7

CODE		SIZES	MAX. FLOW RATE:
NPT	SWEAT	SIZES	(GPM)
<b>5495</b> 06A	<b>5495</b> 96A	1"	11
<b>5495</b> 07A	<b>5495</b> 97A	11/4"	18
<b>5495</b> 08A	<b>5495</b> 98A	1½"	26
<b>5495</b> 09A	<b>5495</b> 99A	2"	37

PERFORMANCE	
MAX. WORKING PRESSURE	150 psi (10 bar)
WORKING TEMPERATURE RANGE	32 — 210°F (0-100°C)
MAX. PERCENTAGE OF GLYCOL:	50%
AIR SEPARATION EFFICIENCY	100% to micro bubble level
PARTICLE SEPARATION CAPACITY	up to 5 µm (0.2 mil)
FERROUS IMPURITIES REMOVAL EFFI-	up to 100%

#### **OPERATING PRINCIPLE**

#### 1)HYDRAULIC SEPARATION




2) AIR SEPARATION






#### 3) DIRT SEPARATION



4) MAGNETIC REMOVAL OF FERROUS IMPURITIES



### APPLICATION DIAGRAM



REFERENCE DOCUMENTATION: TECHNICAL BROCHURE 01249



