

MOTORIZED ZONE VALVES



Z2 2-way

tech. broch. 01115

Two-way on/off two position valve.
Straight through flow pattern.
Brass body.
Stainless steel stem.
EPDM rubber seals and paddle.
Max. working pressure: 300 psi.
Max temperature: 240°F.



Z3 3-way

tech. broch. 01115

Three-way on/off two position valve.
Diverging flow pattern.
Brass body.
Stainless steel stem.
EPDM rubber seals and paddle.
Max. working pressure: 300 psi.
Max temperature: 240°F.

Code	Description	Cv	Δ P	Lbs	USD
Z200041	Inverted Flare	1.0	75 psi	1.1	63.70
Z200042	Inverted Flare	2.5	50 psi	1.1	63.70
Z200043	Inverted Flare	3.5	30 psi	1.1	63.70
Z200053	½" SAE Flare	3.5	30 psi	1.1	82.00
Z200411	½" NPT	1.0	75 psi	1.1	63.70
Z200412	½" NPT	2.5	50 psi	1.1	63.70
Z200413	½" NPT	3.5	30 psi	1.1	63.70
Z200431	½" sweat	1.0	75 psi	1.0	58.40
Z200432	½" sweat	2.5	50 psi	1.0	58.40
Z207433*	½" sweat LF	3.5	30 psi	1.0	82.00
Z200512	¾" NPT	2.5	50 psi	1.2	87.40
Z200513	¾" NPT	3.5	30 psi	1.2	87.40
Z200515	¾" NPT	5.0	25 psi	1.2	87.40
Z200517	¾" NPT	7.5	20 psi	1.2	87.40
Z200532	¾" sweat	2.5	50 psi	1.1	76.90
Z200533	¾" sweat	3.5	30 psi	1.1	76.90
Z207533*	¾" sweat LF	3.5	30 psi	1.1	100.50
Z200535	¾" sweat	5.0	25 psi	1.1	76.90
Z200537	¾" sweat	7.5	20 psi	1.1	76.90
Z207537*	¾" sweat LF	7.5	20 ps	1.1	100.50
Z200617	1" NPT	7.5	20 psi	1.3	137.90
Z200635	1" sweat	5.0	25 psi	1.2	130.00
Z200637	1" sweat	7.5	20 psi	1.2	130.00
Z200737	1¼" sweat	7.5	20 psi	1.3	174.90
Z200687**	1" male union	7.5	20 psi	1.1	87.40

***LF** Low-lead brass body.

** Presscon fitting body.



Two-way and three-way zone valve body repair kit. Includes valve stem paddle with O-rings, C clip and one bottom cap O-ring.

Code	Description	Lbs	USD
F69293	Repair kit for all 1/2" & 3/4" sweat Z2, Z3 valves	0.4	21.90
F69294	Repair kit for 3/4" NPT and all 1" Z2, Z3 valves	0.4	21.90

Code	Description	Cv	Δ P	Lbs	USD
Z300041	Inverted Flare	1.0	75 psi	1.1	84.90
Z300042	Inverted Flare	2.5	50 psi	1.1	84.90
Z300043	Inverted Flare	3.5	30 psi	1.1	84.90
Z300053	½" SAE Flare	3.5	30 psi	1.1	102.00
Z300411	½" NPT	1.0	75 psi	1.1	84.90
Z300412	½" NPT	2.5	50 psi	1.1	84.90
Z300413	½" NPT	3.5	30 psi	1.1	84.90
Z300431	½" sweat	1.0	75 psi	1.0	79.60
Z300432	½" sweat	2.5	50 psi	1.0	79.60
Z307433*	½" sweat LF	3.5	30 psi	1.0	103.30
Z300512	¾" NPT	2.5	50 psi	1.2	106.10
Z300513	¾" NPT	3.5	30 psi	1.2	106.10
Z300515	¾" NPT	5.0	25 psi	1.2	106.10
Z300517	¾" NPT	7.5	20 psi	1.2	106.10
Z300532	¾" sweat	2.5	50 psi	1.1	98.40
Z300533	¾" sweat	3.5	30 psi	1.1	98.40
Z300535	¾" sweat	5.0	25 psi	1.1	98.40
Z307537*	¾" sweat LF	7.5	20 psi	1.0	121.90
Z300617	1" NPT	7.5	20 psi	1.3	159.20
Z300635	1" sweat	5.0	25 psi	1.2	148.40
Z300637	1" sweat	7.5	20 psi	1.2	148.40
Z300737	1¼" sweat	7.5	20 psi	1.3	180.20
Z300687**	1" male union	7.5	20 psi	1.2	111.00

***LF** Low-lead brass body.

** Presscon fitting body.

NA605



Wall transformer.
Input voltage: 120 V AC
Output voltage: 24 V AC.
Power output: 40 VA.
Agency approval: cULus

Code	Description	Lbs	USD
NA605010	24 VAC wall transformer	1.0	46.60