

PRESSURE REDUCING VALVES



535H PresCal™ PEX

Pressure reducing valve for residential and commercial applications.
Max. working pressure: 300 psi.
Max. working temperature: 180°F.
Pressure setting range: 15 — 90 psi.
PEX crimp: ASTM F1807.
PEX expansion: ASTM F1960.
Front and back set point indication for visibility in any mounting orientation.
UV protective cover included.

Code	Description	Min GPM	Max GPM	Lbs	USD
535750HA	¾" PEX crimp union	2.1	12.5	2.3	122.00
535751HA*	¾" PEX crimp union	2.1	12.5	2.4	133.00
535550HA	¾" PEX expansion union	3.2	19	2.3	122.00
535551HA*	¾" PEX expansion union	3.2	19	2.4	133.00
535760HA	1" PEX crimp union	2.1	12.5	3.0	160.00
535761HA*	1" PEX crimp union	2.1	12.5	3.1	171.00
535560HA	1" PEX expansion union	3.2	19	3.0	160.00
535561HA*	1" PEX expansion union	3.2	19	3.1	171.00

GPM flowrate at 6 feet per second water velocity.
*With gauge



PVC jumper nipple with male union thread. The length of the jumper nipple matches the 535H series valve body face-to-face dimension (B"), allowing the piping to be completed prior to the installation of valve and permitting quick change out from the jumper to the valve.

Code	Description	Lbs	USD
NA11304	Jumper nipple for 535H ½"	0.1	14.70
NA11305	Jumper nipple for 535H ¾"	0.1	16.20
NA11306	Jumper nipple for 535H 1"	0.2	17.30
NA11307	Jumper nipple for 535H 1¼"	0.3	18.60
NA11308	Jumper nipple for 535H 1½"	0.3	20.30
NA11309	Jumper nipple for 535H 2"	0.5	58.50

Complies with: ASSE 1003, CSA B356, NSF/ANSI/CAN 61, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes. Plenum rated: compliant with the requirements of standard UL 2043.



535H PresCal™ Body

Replacement valve body.
DZR low lead "Ecobrass" body.
Gauge port plug NA10438 included with body.
See fitting selection table in Section 8.

Code	Description	Lbs	USD
NA535840HA	½" body	1.9	84.90
NA535841HA	½" body, gauge	2	96.00
NA535850HA	¾" body	2.2	89.40
NA535851HA	¾" body, gauge	2.3	100.00
NA535860HA	1" body	2.9	118.00
NA535861HA	1" body, gauge	3.0	129.00
NA535870HA	1¼" body	6.1	258.00
NA535871HA	1¼" body, gauge	6.2	269.00
NA535880HA	1½" body	7.3	364.00
NA535881HA	1½" body, gauge	7.4	375.00
NA535890HA	2" body	9.7	422.00
NA535891HA	2" body, gauge	9.8	434.00

Order body with custom fittings.



Replacement cartridge for 535H series pressure reducer.

Code	Description	Lbs	USD
535006HA	Fits 535H ½", ¾", 1"	0.3	62.60
535009HA	Fits 535H 1¼", 1½", 2"	0.5	189.00