

Specifications



Photo is representative



Eaton FRN-R-3-2/10

Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 3.2 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series FRN-R fuse
CATALOG NUMBER	FRN-R-3-2/10
UPC	051712507189
PRODUCT LENGTH/DEPTH	3 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked
PRODUCT TYPE	Fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	3.2 A
INTERRUPT RATING	20 kAIC at 125 Vdc 200 kAIC at 250 Vac
RESPONSE TIME	8 sec at 500%
VOLTAGE RATING	250 Vac, 125 Vdc

General information

CLASS	Class RK5
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Finger safe

Physical details

NUMBER OF ELEMENTS	Dual
PACKAGING TYPE	Standard

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL SERVICE BULLETINS	Bussmann series Fusetron FRN-R RK5 fuse data sheet for up to 60 amps No. 1019

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

