

Specifications



Photo is representative



Eaton SC-40

Eaton Bussmann Series Class G fuse, SC, fast-acting, current limiting fuse, 40 A, rejection style fuse, interrupting rating of 100 kA at 480 Vac and 10 kA at 300 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	SC-40
UPC	051712250405
PRODUCT LENGTH/DEPTH	2.25 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.35 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
PRODUCT TYPE	Fuse

Electrical rating

AMPERAGE RATING	40 A
INTERRUPT RATING	100 kAIC at 480 Vac 10 kAIC at 300 Vdc
RESPONSE TIME	12 sec at 200%
VOLTAGE RATING	480 Vac, 300 Vdc

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Ferrule design, Type P

Physical details

PACKAGING TYPE	Standard
----------------	----------

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter
	Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL DATA SHEETS	Bussmann series Rejecting Fuses data sheet no. 1024

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

