


Dura-Power MANIFOLD KITS

MODELS DVE-52, 80, 120 AND DRE-52, 80, 120, AND DSE-65, 80, 100, 120

Precision cut type "L" all copper tube manifold kits assure water flow balance of all units. Without this balance, the full water heating and storage potential of the system cannot be achieved. All tubing, elbows and valves required for manifold construction as illustrated are contained in the kit.

Dimensions shown are for minimum space occupied by complete assemblies. Service space in front of the units must be added. The manifold kits are provided with gate valves to isolate units for servicing.




ALL DIMENSIONS IN INCHES

TWO HEATERS

Model	Part Number	H	W	D	A
DRE/DVE-52	9003429205	66-1/4	56-3/4	27-1/4	13-1/4
DRE/DVE-80		70-1/2	60-1/4	31-1/4	9-3/4
DRE/DVE-120		73-1/4	64-1/2	35-3/4	5-1/2
DSE-6		61-1/2	59-1/2	30-1/4	10-1/2
DSE-80		60-1/4	61-1/2	32-1/4	8-1/2
DSE-100		69-1/4	61-1/2	32-1/4	8-1/2
DSE-120		74-1/4	63	33-3/4	7


Inlet and Outlet Size - 1-1/2



THREE HEATERS

Model	Part Number	H	W	D	A
DRE/DVE-52	9003430205	66-1/4	91-3/4	27-1/4	13-1/4
DRE/DVE-80		70-1/2	95-1/4	31-1/4	9-3/4
DRE/DVE-120		73-1/4	99-1/2	35-3/4	5-1/2
DSE-65		61-1/2	94-1/2	30-1/4	10-1/2
DSE-80		60-1/4	96-1/2	32-1/4	8-1/2
DSE-100		69-1/4	96-1/2	32-1/4	8-1/2
DSE-120		74-1/4	98	33-3/4	7

Inlet and Outlet Size - 2-1/2



FOUR HEATERS

Model	Part Number	H	W	D	A
DRE/DVE-52	9003431205	66-1/4	126-3/4	27-1/4	13-1/4
DRE/DVE-80		70-1/2	130-1/4	31-1/4	9-3/4
DRE/DVE-120		73-1/4	134-1/2	35-3/4	5-1/2
DSE-65		61-1/2	129-1/2	30-1/4	10-1/2
DSE-80		60-1/4	131-1/2	32-1/4	8-1/2
DSE-100		69-1/4	131-1/2	32-1/4	8-1/2
DSE-120		74-1/4	133	33-3/4	7

Inlet and Outlet Size - 2-1/2

COMMERCIAL ELECTRIC WATER HEATER COMPARISON TABLE

Model ¹ A. O. Smith	Approvals	³ Max. KW									Element Operation ³	Tank Work Press.	Maximum Thermostat Setting (°F)	Separate Control Circuit Has Contactor(s)	Application Notes ⁶				
			208		240		277		480										
			1	2	1	3	1	1	3	3									
DEL/DEN-30	UL	12									Two element interlocking or convertible to two element simultaneous.	150	170		Interlocking circuit figure recovery of one element only. Simultaneous circuit figure upper element recovery at 1/3 capacity and lower element at full capacity.				
DEL/DEN-40	ASHRAE	12																	
DEL/DEN-50	90A-1980	12		X ²		X ²			X ²										
DEN-66		12																	
DEN-80		12																	
DEN-120		12																	
DRE-52	UL NSF	36									Each element has thermostat surface mounted.	150	180		2/3/4 heater manifold kits with valves available.				
DRE-80	ASHRAE	54	X +	X +	X +	X +	X +	X +	X +										
DRE-120	90A-1980 CSA	54																	
DSE-5	UL NSF	3									Simultaneous or optional thermostat "step" control or time delay sequencer.	150	180	X (120 Volts)					
DSE-10	ASME	6																	
DSE-20	NB	18																	
DSE-30	ASHRAE	24	X •	X	X •	X	X	X •	X										
DSE-40	90.1b/1992	36								⁷									
DSE-50		90																	
DSE-65		90	X •																
DSE-80		90																	
DSE-100		90																	
DSE-120		90																	
		90 kw max.																	
CMC (5 gallons)	UL NSF	54	X +	X ⁵	X +	X ⁵	X	X +	X	Simultaneous	150	194	X (120 Volts)	Primarily booster heaters for dishwasher rinse.					
	NB ASME																		
(20 gallons)	CSA	54	X •	X	X •	X	X	X •	X	Simultaneous	150	194							
DVE-52	UL NSF	54								Simultaneous or optional thermo- stat "step" con- trol.	150	180	X (120 Volts)	2/3/4 heater manifold kits with valves available.					
DVE-80	ASHRAE	54	X +	X +	X +	X +	X	X +	X +										
DVE-120	90A-1980 CSA 8	54																	
DVE-125		120								Simultaneous (1 thermostat for 60 kw) or optional thermostat "step" control or time delay sequencer or modulating step control.	(Std.) 125 (Opt.) 150 or 160	180	X (120 Volts)	"DHE" models for horizontal installation 200 gallons and above.					
DVE-150 or 15L		150																	
200		180	X	XN	X														
DVE-250		240																	
DVE-300	UL	300																	
DHE-350	ASME	330																	
400	NB	390																	
500	ASHRAE	480																	
600	90.1b-1992	600																	
700		660																	
800		720																	
1000		990													⁷				
Larger units available. (See catalog).																			
			208		240		277		480						600				
			1	3	1	3	1	3	1	3	3								

¹ The model number indicates the normal tank size in U.S. gallons. Exceptions: 120 which is listed as 119 gallons.

² Unbalanced 3 Ø - convertible to 1 Ø.

³ Recovery based on full kw operation for one hour.
Figured at 1 kw 4.1 gallons @ 100°F rise.

⁴ + Convertible to 1 Ø or 3 Ø.
• Convertible to 3 Ø.

⁵ Condition phase convertability, see spec. sheet.

⁶ All are for general purpose hot water and can be used for dishwasher rinse (except DEL/DEN), also check Approvals column if NSF is required.
Only special application notes are listed.

⁷ Y connected elements operate at 277 volts 1 Ø in 480 volt 3 Ø circuit.

⁸ CM model CSA listed only.