



2171LF

see what Delta can do™

BAR & PREP SINK FAUCETS

■ Two Handle, Deck Mount



STANDARD SPECIFICATIONS:

- Max. flow rate 1.5 gpm @ 60 psi, 5.7 L/min @ 414 kPa.
- Two handle bar sink faucet for exposed mounting on 2 and 3 hole sinks with 4" centers
- Spout swivel 360˚
- All operating parts shall be replaceable from the top
- Hot and cold stems are interchangeable
- 1/2"-14 NPSM threaded male inlet shanks
- Control mechanism is a rotating cylinder type with stainless steel plate and 90˚ rotating, with replaceable non-metallic seats.

WARRANTY

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.


COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- NSF/ANSI/CAN 61 & 372
- ICC/ANSI A117.1

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-S-2171LF Rev. F

Delta Faucet Company
55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2026 Delta Faucet Company




2171LF

voyez ce que Delta peut faire™

BAR ET PRÉPARATION ROBINETS D'ÉVIER

■ Deux poignées, installation sur plan



SPÉCIFICATIONS STANDARDS :

- Débit maximal de 1,5 gal./min à 60 psi, 5.7 L/min à 414 kPa.
- Robinet de bar à deux poignées pour installation exposée sur éviers à 2 ou 3 trous avec entraxe de 4 po (102 mm)
- Bec pivotant à 360˚
- Toutes les pièces de fonctionnement peuvent être remplacées par le dessus
- Les tiges de l'eau chaude et froide sont interchangeables
- Tiges d'entrée mâles filetées 1/2 po (13 mm) - 14 NPSM
- Le mécanisme de contrôle est un cylindre rotatif avec plaque en acier inoxydable et rotation de 90˚, avec des sièges non métalliques remplaçables.

GARANTIE

- Pièces et finition – Garantie à vie limitée; ou pour les clients commerciaux, 10 ans pour les résidences multifamiliales (appartements et condominiums) et 5 ans pour tout autre usage commercial, dans tous les cas à compter de la date de réception du produit par l'acheteur initial ou son représentant autorisé (installateur, etc.).
- Veuillez consulter le site fr.deltafaucet.ca pour tous les détails de notre garantie limitée.

CONFORME À :

- ASME A112.18.1 / CSA B125.1
- NSF/ANSI/CAN 61 et 372
- ICC/ANSI A117.1

Delta Faucet Company se réserve le droit (1) d'effectuer des changements dans les spécifications et les matériaux, et (2) de modifier ou d'abandonner certains modèles, dans les deux cas sans préavis ni obligation. Les dimensions sont à titre indicatif seulement. Consultez le Livre des prix courants de la gamme complète ou fr.deltafaucet.ca pour les options de finition et la disponibilité des produits.

DSP-S-2171LF Rév. F

Delta Faucet Company
55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2026 Delta Faucet Company