



HB

CONSTANT WATTAGE, PRE-TERMINATED CABLE

HB is a 120 Vac resistance heating cable that includes ground braid, a black outer jacket, and a two-foot orange 14/3 cold lead with no thermostat or plug. Cables are rated at 7 watts per foot. HB cables are UL Listed to Canadian Safety Standards and CSA Certified.





CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
HB01	3.28' length, 23 watts	20	10	0-69996-00332-7	 
HB02	6.56' length, 46 watts	20	12	0-69996-00333-4	
HB03	9.84' length, 69 watts	20	15	0-69996-00334-1	
HB04	13.12' length, 92 watts	20	17	0-69996-00335-8	
HB05	16.41' length, 115 watts	20	20	0-69996-00336-5	
HB06	19.69' length, 138 watts	20	24	0-69996-00337-2	
HB07	22.97' length, 161 watts	10	13	0-69996-00338-9	
HB09	29.53' length, 207 watts	10	15	0-69996-00339-6	
HB12	39.37' length, 275 watts	10	17	0-69996-00340-2	
HB18	59.06' length, 414 watts	10	18	0-69996-00341-9	
HB24	78.74' length, 551 watts	10	21	0-69996-00342-6	

HB2

CONSTANT WATTAGE, PRE-TERMINATED CABLE

HB2 is a 240 Vac resistance heating cable that includes ground braid, a black outer jacket, and a two-foot orange 14/3 cold lead with no thermostat or plug. Cables are 7 watts per foot. HB2 cables are UL Listed to Canadian Safety Standards and CSA Certified.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
HB022	6.56' length, 46 watts	20	13	0-69996-00343-3	 
HB042	13.12' length, 92 watts	20	17	0-69996-00344-0	
HB062	19.69' length, 138 watts	20	21	0-69996-00345-7	
HB082	26.25' length, 184 watts	10	14	0-69996-00346-4	
HB102	32.81' length, 230 watts	10	17	0-69996-00347-1	
HB122	39.37' length, 275 watts	10	21	0-69996-00348-8	
HB142	45.93' length, 321 watts	5	14	0-69996-00349-5	
HB182	59.06' length, 414 watts	5	15	0-69996-00350-1	
HB242	78.74' length, 551 watts	5	20	0-69996-00351-8	