



## Residential (Dry Location) Pipe Freeze Prevention



Reel Lengths  
100 ft • 300 ft • 500 ft



### Self-Regulating, Cut-to-Length Pipe Tracing Cable

**Freeze Free® Cable** — Self-regulating pipe heating cable that automatically varies its heat output with changes in surrounding temperature. Freeze Free® cable helps keep plastic and metal water pipes from freezing to -60°F/-51°C. A braided metal jacket provides an electrical ground as well as protection against damage in dry locations. Freeze Free cable is available on reels of 100', 300' and 500' and can be cut to desired lengths per application. Pre-packaged lengths of 5 feet and 15 feet are also available. 3 watts/ft, 120 VAC at 50°F; 75' maximum circuit length, 3' minimum circuit length.

**Freeze Free® Fused Plug and End Seal (10802)** — This connection kit provides the specially designed fused plug to connect one Freeze Free® heater into an electrical outlet and a cable end seal. Helps ensure safe and proper usage of the Freeze Free cable.



10802 Plug End Seal Kit

PART #	DESCRIPTION	CTN QTY	CTN WGT	UPC
2102	100' reel Freeze Free	1	5	0-13627-06895-7
2302	300' reel Freeze Free	1	13	0-13627-06896-4
2502	500' reel Freeze Free	1	20	0-13627-06894-0
10802	Connection Kit — Clamshell	10	3	0-13627-10802-8
10803	Connection Kit — Polybagged	25	5	0-13627-10803-5
FFEC	End Seals — 5/bag	10	2	0-13627-06946-6
10805	5' prepackaged Freeze Free Kit	5	4	0-13627-10805-9
10815	15' prepackaged Freeze Free Kit	5	6	0-13627-10815-8
4102	100' Display: (1) reel; (10) 10802	1	8	0-13627-06897-1
4302	300' Display: (1) reel; (20) 10802; (10) EH-38; (10) HCA	1	17	0-13627-06898-8
NPRO-50	50' Pro Pack: (1) reel; (3) 10803; (1) HCA	1	3	0-13627-10798-4
NPRO-100	100' Pro Pack: (1) reel; (6) 10803; (1) HCA	1	6	0-13627-10799-1



4302 Display

### Freeze Free® Accessories

**Freeze Free® Application Tape (HCA)** — Application Tape. The best tape to use with Freeze Free® cable. Thirty feet of clear tape, rated for temperature so as not to lose its adhesive properties, printed with the words ELECTRICALLY HEATED PIPE for easy identification. One per package. 1/2" x 10 yards.

**EH-38 Pre-set Thermostat** — Automatically energizes heating cable at temperatures lower than 38°F/3°C, eliminates the need for unplugging heating cables each spring and reduces the risks of frozen pipes. EH-38 can control other electrical devices that need to be activated when the temperature approaches the freezing point. 15 amps, resistive load at 125 VAC. UL, cUL.

**CS** — Caution Labels. Reduces possibility of accidents and liability with easy-to-read caution labels. Five per bag.

PART #	DESCRIPTION	CTN QTY	CTN WGT	UPC
HCA	Application Tape: 1/2" x 30'	10	2	0-13627-06945-9
EH-38	Pre-set Thermostat; UL cUL	10	3	0-13627-09938-8
CS	Heated Pipe Caution Labels, 5 per bag	1	.25	0-13627-09924-1



EH-38 Pre-set Thermostat