

Eaton C25BNB230A

Catalog number: C25BNB230A

Eaton definite purpose contactor, Mounting plate, Quick, 25A, Quick connect (side-by-side), 110-120 Vac, 50/60 Hz, Open with metal mounting plate, Compact, 25A, Contactor, Two-pole, 50 pc./pkg., F1, Binding head screw, Non-reversing

General specifications



Product Name	Catalog Number
Eaton definite purpose contactor	C25BNB230A
UPC	Product Length/Depth
786685116020	2.32 in
Product Height	Product Width
3.19 in	1.97 in
Product Weight	Warranty
.6 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized CSA Certified

defaultTaxonomyAttributeLabel

Frame size

Compact, two-pole

Type

Non-reversing

Inductive full load

30 A

Model

Contactors

Connection

Quick

Enclosure

Open with metal mounting plate

Terminals

Binding head screw and quick connect terminals (side-by-side)

Amperage Rating

30A

Resistive load

40 A

Number Of Poles

Two-pole

Coil

110-120 Vac, 50/60 Hz

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25BNB 3D Inventor](#)

[C25BNB AutoCAD 2D Footprint \(mm\)](#)

[C25BNB 2D Drawing Xchange](#)

[C25BNB 2D PDF](#)

[C25BNB 3D Model Xchange](#)

[C25BNB AutoCAD 2D Footprint](#)

Specifications and datasheets

[Eaton Specification Sheet - C25BNB230A](#)

[Quick Selector - Definite Purpose Contactors](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)