

Specifications



Eaton DH364URK

Eaton Heavy duty single-throw non-fused safety switch, Single-throw, 200A, NEMA 3R, Painted galvanized steel, Non-Fusible, Three-pole, Three-wire, 15 at 240 Vac TD 1 Ph, 50 at 480 Vac TD 1 Ph, 50 at 600 Vac TD 1 Ph, 60 at 240 Vac TD 3 Ph

General specifications

PRODUCT NAME	Eaton heavy duty non-fusible safety switch
CATALOG NUMBER	DH364URK
UPC	782113206813
PRODUCT LENGTH/DEPTH	11.25 in
PRODUCT HEIGHT	27.63 in
PRODUCT WIDTH	16 in
PRODUCT WEIGHT	35 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEC 230.62 (C) Compliant Barrier
CERTIFICATIONS	UL Listed
CATALOG NOTES	Suitable for service entrance use with a neutral or ground lug kit installed

Physical Attributes

ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Non-fusible
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
TYPE	Single-throw

Miscellaneous

PRODUCT CATEGORY	Heavy Duty, Non-Fusible
UTILITY APPROVALS	NM : Public Service Company of New Mexico (PNM)

Performance Ratings

AMPERAGE RATING	200A
HP RATING - MAX	15 at 240 Vac TD 1 Ph, 50 at 480 Vac TD 1 Ph, 50 at 600 Vac TD 1 Ph, 60 at 240 Vac TD 3 Ph, 125 at 480 Vac TD 3 Ph, 150 at 600 Vac TD 3 Ph, 40 at 250 Vdc
NEMA RATING	NEMA 3R
VOLTAGE RATING	600 V

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DH364URK

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.