


FIG. 41CT EPOXY COATED (COPPER-GARD) COPPER TUBE SPLIT RING EXTENSION HANGER



Material: Malleable iron.

Finish: Copper epoxy coated (COPPER-GARD). COPPER-GARD products offer superior corrosion protection due to the epoxy coating over electro-galvanized material. The alternative copper plating that has been done historically identifies the product and is not intended for protection. Refer to MSS SP58, 13.3.


Service: Designed for the suspension of non-insulated stationary copper tubing, horizontally or vertically.

Approvals: Complies with Federal Specification WWH-171-E (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 and MSS SP-69 (Type# 12).

Ordering: Specify tube size and figure number.

TUBE SIZE	TUBE OD	SCREW	A	B	C	D	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.625	10-24	3/8-16	11/16	1 7/8	1 1/8	0.087	180
3/4	0.875	10-24	3/8-16	13/16	2 1/4	1 3/8	0.096	180
1	1.125	10-24	3/8-16	15/16	2 1/2	1 5/8	0.128	180
1 1/4	1.375	10-24	3/8-16	1 1/16	2 7/8	1 7/8	0.141	180
1 1/2	1.625	10-24	3/8-16	1 3/16	3	2 3/16	0.179	180
2	2.125	10-24	3/8-16	1 7/16	3 1/2	2 11/16	0.229	180

FIG. 41H SPLIT RING EXTENSION HANGER, HINGE DESIGN



Material: Malleable iron.

Finish: Plain, electro-galvanized.

Service: Designed for the suspension of non-insulated stationary pipe lines horizontally or vertically.

Approvals: Complies with Federal Specification WWH-171-E (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 and MSS SP-69 (Type# 12).

Ordering: Specify pipe size, figure number and finish.

PIPE SIZE	PIPE OD	SCREW	A	B	C	D	WGT EACH (lbs)	MAX REC LOAD (lbs)
3/8	0.675	10-24	3/8-16	11/16	1 13/16	1 3/16	0.084	180
1/2	0.840	10-24	3/8-16	3/4	2 1/8	1 3/16	0.098	180
3/4	1.050	10-24	3/8-16	7/8	2 1/2	1 9/16	0.112	180
1	1.315	10-24	3/8-16	1 1/8	2 3/4	2	0.147	180
1 1/4	1.660	10-24	3/8-16	1 5/16	3 3/16	2 3/8	0.181	180
1 1/2	1.900	10-24	3/8-16	1 7/16	3 3/8	2 5/8	0.214	180
2	2.375	10-24	3/8-16	1 5/8	3 15/16	3 1/16	0.299	180
2 1/2	2.875	1/4	1/2-13	2 1/8	5 3/16	3 13/16	0.583	300
3	3.500	1/4	1/2-13	2 1/2	5 11/16	4 5/8	0.713	300
4	4.500	1/4	1/2-13	2 7/8	6 3/4	5 9/16	1.019	300