

PEX-a Pipe Support

Submittal Information

Revision B: June 10, 2013

Project Information

Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

Technical Data

Material: Commercial-grade (Type B) galvanized steel



Product Information and Application Use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths.

✓ Description	Part Number	Height	Width	Length	Gauge	Weight
½" PEX-a Pipe Support, 9-ft. length	F7040500	0.42"	0.75"	108"	23	1.10 lbs.
¾" PEX-a Pipe Support, 9-ft. length	F7040750	0.56"	1.00"	108"	23	1.50 lbs.
1" PEX-a Pipe Support, 9-ft. length	F7041000	0.64"	1.13"	108"	23	1.91 lbs.
1¼" PEX-a Pipe Support, 9-ft. length	F7041250	0.79"	1.38"	108"	23	2.10 lbs.
1½" PEX-a Pipe Support, 9-ft. length	F7041500	0.93"	1.63"	108"	23	2.50 lbs.
2" PEX-a Pipe Support, 9-ft. length	F7042000	1.14"	2.00"	108"	23	3.60 lbs.

Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

Standards

ASTM E84

Codes

IMC, UMC, NBCC

Listings

cQAIus

Related Applications

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems
AquaSAFE™ Fire Safety Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
www.uponorpro.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
www.uponorpro.com