RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.

RIBXG420-100
Enclosed 100A Current Sensor w/ Loop
Powered 4-20mA Transmitter Output
Bulletin B1253 • 393124A

UL508
UL864

Functional Devices, Inc.™
www.FunctionalDevices.com

- Optional mounting tab may be removed.
- Racheting Cam may be closed against load wire to secure RIBXG420-100 in position.



ACCURACY	MAX OUTPUT CURRENT
99% FS (20%-100% Span)	30mA
WIRES	LINEARITY
18AWG, 600V Rated	99% FS (20%-100% Span)

CAUTION: RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DEENERGIZE THE DEVICE BEFORE SERVICING.