For Residential and Commercial Applications				
Job Name		Engineer / Architect		
Job Location		Wholesaler		
Submittal Date		Contractor		

G2BRPX19 1/4 Turn Angle Stop – Barbed PEX x Compression

Use: For use in potable water distribution systems. Not intended for recirculating systems that produce continuous use temperatures above 115° F. For those applications, use our KTTM series ball stop.

Design Features:


- One-piece shut-off mechanism provides smooth on-off operation without freeze ups even after long periods of non-use
- Positive 1/4 turn shut off
- Full-flow operation with no waterway obstructions
- Corrosion-resistant handle is plated in an attractive chrome finish
- Machined, one-piece brass body provides strength, durability, and long-lasting performance
- Easy-to-remove handle with screw attachment helps protect against accidental operation during rough-ins
- 100% Leak tested
- W No Lead
- PEX end designed to ASTM F1807
- **For use with** ASTM F876 PEX tubing, in ASTM F877 water distribution systems using ASTM F1807, and/or F2098 connection methods

Operating Specifications:

Temperature: 40°-140° F

Pressure: 125 PSI maximum

STOP MATERIAL SPECIFICATIONS			
Body	Brass or brass, chrome plated		
Stem Barrel	Rubber		
Stem Shaft	Glass-filled polypropylene		
O-ring	Rubber		
Handle	Zinc die cast, chrome plated		
Screw	Zinc-plated steel		
Compression Nut	Brass or brass, chrome plated		
Compression Sleeve	Brass		








G2BRPX19 1/4 Turn Angle Stop – Barbed PEX x Compression

Part Listing:

G2BRPX19X C 1/2" nom crimp barb (for PEX) x 3/8" OD compression, chrome plated

G2BRPX19L1X CB 1/2" nom crimp barb (for PEX) x 3/8" OD compression, less nut, chrome plated, bulk

1/2" nom crimp barb (for PEX) x 3/8" OD compression, rough brass G2BRPX19X R



PART DIMENSIONS (Inches)				
Model	DIM. A	DIM. B		
G2BRPX19X	1.02	2.06		
G2BRPX19L1X	.74	2.06		

Listings & Certifications:

- IAPMO listed to ASME A112.18.1 / CSA B125.1 (File # 0645)
- CSA listed to ASME A112.18.1 / CSA B125.1 (File # 204593)
- No-Lead product CSA listed to Low Lead Content Certification Program - Plumbing Products Class 6853-01









