




SUBMITTAL DATA

FXE36HP230V1R32AH / FXE36HP230V1R32AO
36000 BTU/H Unitary Heat Pump Split System

| | | |
|------------------|--------------|------|
| Job Name | Location | Date |
| Purchaser | Engineer | |
| Submitted to | For | |
| Unit Designation | Schedule No. | |

| | | |
|--|---|--|
|  <p>FXE36HP230V1R32AH</p> |  <p>FXE36HP230V1R32AO</p> |  <p>WK-010WC1</p> |
|--|---|--|


GENERAL FEATURES

- AHRI Certificate: 216626009
- High Efficiency DC Inverter Technology
- Zero Lot Line Design
- Operation Range: 5°F ~ 118°F
- New R32 Refrigerant
- WK-010WC1 Programmable Wired Controller Included
- Multi-Position Air Handler
- RS485 Communication and Universal 24V Control
- Coil (Outdoor) Copper Tube/Aluminum Fin with Anti-Corrosion Coil Coating (Gold Colored Fin - 1500Hr Salt Spray Rating)
- Coil (Indoor) Copper Tube/Aluminum Fin with Anti-Corrosion Coil Coating (Blue Colored Fin - 500Hr Salt Spray Rating)

SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

| SPECIFICATIONS | | FXE36HP230V1R32AH / FXE36HP230V1R32AO | | FEATURES & FUNCTIONS SUMMARY | | FXE36HP230V1R32AH / FXE36HP230V1R32AO | | | | |
|---|----------------------|---|---------------------------|------------------------------------|--|---------------------------------------|--|-------------|-------------------|--|
| System Type | | HEAT PUMP | | Compressor | | Inverter | | | | |
| SYSTEM PERFORMANCE | | | | Ultra Low Frequency Torque Control | | | | Yes | | |
| Cooling Capacity | Min - Max | Btu/h | 17,000 - 37,400 | | Power Factor Correction | | | | Yes | |
| | Rated Capacity @95°F | Btu/h | 34,000 | | Compressor Type | | | | Rotary | |
| Heating Capacity | Min - Max | Btu/h | 17,000 - 38,000 | | Electronic Expansion Valve (EEV) | | | | Yes | |
| | Rated Capacity @47°F | Btu/h | 34,000 | | Basepan With Electric Heater | | | | Yes | |
| | Rated Capacity @17°F | Btu/h | 27,400 | | Compressor With Electric Heater | | | | Yes | |
| | Rated Capacity @5°F | Btu/h | 21,600 | | Fin Coating (Outdoor - Golden & Indoor - Blue) | | | | Acrylic Resin | |
| SEER2 | | 19.0 | | Intelligent Defrosting | | | | Yes | | |
| EER2 | | 11.7 | | Intelligent Preheating | | | | Yes | | |
| HSPF2 | | 8.3 | | Low Voltage Startup | | | | Yes | | |
| COP @5°F | | 2.0 | | Memory/Power Failure Recovery | | | | Yes | | |
| COP @47°F | | 3.5 | | Self Diagnosis | | | | Yes | | |
| Cooling Temperature Range | | °F | 5 - 118 | | Low Ambient Cooling | | | | No | |
| Heating Temperature Range | | °F | 5 - 75 | | 24VAC Thermostat Compatible | | | | Yes | |
| Refrigerant Type | | R32 | | Indoor Fan Type | | | | Centrifugal | | |
| INDOOR UNIT | | FXE36HP230V1R32AH | | Multi Fan Speeds | | | | 5 | | |
| Power Supply | | VAC | 208-230V / 1Ph / 60 Hz | | Auxiliary Electrical Heater | | | | Optional | |
| Sound Pressure Level | | dB(A) | 51 | | A2L Leak Detection Sensor (Indoor) | | | | Factory Installed | |
| Control Voltage | | VAC | 24 | | | | | | | |
| MOCP | | A | 15 | | | | | | | |
| MCA | | A | 5.3 | | | | | | | |
| Electric Heater (Optional) | | kW | 6, 9, 12 | | | | | | | |
| Air Flow | | CFM | 1000 | | | | | | | |
| External Static Pressure (Up to) | | In W.c. | 1.0 | | | | | | | |
| Dehumidification | | pt/hr | 6.02 | | | | | | | |
| Drain Piping | | in | Φ1×0.05 | | | | | | | |
| External Dimensions (W x H x D) | | in | 21-1/4 × 21-1/4 × 48-3/16 | | | | | | | |
| Package Dimension (W x H x D) | | in | 23-3/4 × 26 × 50-3/8 | | | | | | | |
| Net Weight | | lbs | 163.1 | | | | | | | |
| Gross Weight | | lbs | 178.6 | | | | | | | |
| OUTDOOR UNIT | | FXE36HP230V1R32AO | | | | | | | | |
| Power Supply | | VAC | 208-230V / 1Ph / 60 Hz | | | | | | | |
| Sound Pressure Level | | dB(A) | 60 | | | | | | | |
| Control Voltage | | VAC | 24 | | | | | | | |
| Rated Current Cooling | | A | 17.5 | | | | | | | |
| Rated Current Heating | | A | 11.5 | | | | | | | |
| MOCP | | A | 25 | | | | | | | |
| MCA | | A | 21.6 | | | | | | | |
| Compressor Type | | GREE G20 / Double Cylinder / 1 - Stage Inverter | | | | | | | | |
| External Dimensions (W x H x D) | | in | 36-1/4×14-9/16×29-3/8 | | | | | | | |
| Package Dimension (W x H x D) | | in | 42-1/2 × 19 × 31-1/2 | | | | | | | |
| Net Weight | | lbs | 124.6 | | | | | | | |
| Gross Weight | | lbs | 133.4 | | | | | | | |
| Refrigerant Charge - R32 | | oz | 98.8 | | | | | | | |
| Additional Charge | | oz/ft | 0.215 | | | | | | | |
| REFRIGERANT PIPING | | | | | | | | | | |
| Line Set Size (Liquid - Gas) - Flared Connections | | in | 3/8 - 3/4 | | | | | | | |
| Pre-Charge Length | | ft | 31 | | | | | | | |
| Pipe Length (Min - Max) | | ft | 10 - 98 | | | | | | | |
| Max. Pipe Elevation | | ft | 49 | | | | | | | |

FAN PERFORMANCE



NOTE:


1. Above chart CFM ratings are based on dry coil with factory filter installed.
2. For wet coil CFM ratings, multiply the CFM by 0.96 correction factor.

DIMENSIONS

INDOOR UNIT

Unit: inch


| FXE36HP230V1R32AH | |
|-------------------|---------|
| DIMENSIONS | |
| A | 11-5/8 |
| B | 20 |
| H | 48-3/16 |
| W | 21-1/4 |
| D | 21-1/4 |




OUTDOOR UNIT

Unit: inch

| FXE36HP230V1R32AO | |
|-------------------|----------|
| DIMENSIONS | |
| A | 39-3/8 |
| B | 16-13/16 |
| C | 29-3/8 |
| D | 24 |
| E | 15-9/16 |
| F | 36-1/4 |
| G | 14-9/16 |



ACCESSORY HEATER AND GENERAL INFORMATION





| MODEL | Heat Kit Model | Part Number | Electric Heat (kW) | | Min. Circuit Ampacity (A) | | | | Max Fuse or Breaker (A) | | | | |
|-------------------|------------------|--------------|--------------------|------|---------------------------|---------|---------|---------|-------------------------|---------|---------|---------|---------|
| | | | 208V | 230V | 208V | | 230V | | 208V | | 230V | | |
| FXE36HP230V1R32AH | One Mains Supply | | | | | | | | | | | | |
| | 320004060223 | FLEXA2LHTR06 | 3.74 | 4.6 | 31 | | 33 | | 35 | | 35 | | |
| | Two Mains Supply | | | | | | | | | | | | |
| | | | | | | Power A | Power B | Power A | Power B | Power A | Power B | Power A | Power B |
| | 320004060224 | FLEXA2LHTR09 | 6.03 | 7.36 | 32.7 | 13.8 | 35.2 | 15 | 35 | 15 | 40 | 20 | |
| 320004060225 | FLEXA2LHTR12 | 7.49 | 9.2 | 32.7 | 27.5 | 35.2 | 30 | 35 | 30 | 40 | 35 | | |

CLEARANCES


INDOOR UNIT

Minimum clearance

| | |
|-------|------|
| FRONT | > 24 |
|-------|------|



Horizontal Left Configuration - No Modification Needed



Horizontal Right Configuration - Must Relocate Drain Pan

NOTE:

Allow a minimum of 24" in front of the unit for service clearance. When installing in an area directly over a finished ceiling (such as an attic), an emergency drain pan is required directly under the unit. **See local and state codes for requirements.** When installing this unit in an area that may become wet, elevate the unit with a sturdy, non-porous material. In installations that may lead to physical damage (i.e. a garage) it is advised to install a protective barrier to prevent such damage. This air handler is designed for a complete supply and return ductwork system.

OUTDOOR UNIT


Minimum clearance

NOTE:

Install the Outdoor Unit **2 Inches** Above the Expected Snow Line

1. When one outdoor unit is to be installed.


| A - E | H_b H_d H | | (in) | | | | |
|------------|---------------|---------------------|------------|-----------|----------|-----------|-----------|
| | | | a | b | c | d | e |
| B | - | - | - | ≥ 4 | - | - | - |
| A, B, C | - | - | ≥ 12 | ≥ 4 | ≥ 4 | - | - |
| B, E | - | - | - | ≥ 4 | - | - | ≥ 40 |
| A, B, C, E | - | - | ≥ 12 | ≥ 6 | ≥ 6 | - | ≥ 40 |
| D | - | - | - | - | - | ≥ 40 | - |
| D, E | - | - | - | - | - | ≥ 40 | ≥ 40 |
| B, D | $H_b < H_d$ | $H_d < H$ | - | ≥ 4 | - | ≥ 40 | - |
| | $H_b > H_d$ | $H_d > H$ | - | ≥ 4 | - | ≥ 40 | - |
| B, D, E | $H_b < H_d$ | $H_b \leq 1/2H$ | - | ≥ 10 | - | ≥ 80 | ≥ 40 |
| | | $1/2H < H_b \leq H$ | - | ≥ 10 | - | ≥ 80 | ≥ 40 |
| | | $H_b > H$ | Prohibited | | | | |
| | $H_b > H_d$ | $H_b \leq 1/2H$ | - | ≥ 4 | - | ≥ 80 | ≥ 40 |
| | | $1/2H < H_b \leq H$ | - | ≥ 8 | - | ≥ 80 | ≥ 40 |
| | | $H_b > H$ | Prohibited | | | | |



CLEARANCES


2. When two or more outdoor units are to be installed side by side.

| A - E | H_b H_d H | | (in) | | | | |
|------------|-----------------|---------------------|------------|-----------|-----------|------------|-----------|
| | | | a | b | c | d | e |
| A, B, C | - | | ≥ 12 | ≥ 12 | ≥ 40 | - | - |
| A, B, C, E | - | | ≥ 12 | ≥ 12 | ≥ 40 | - | ≥ 40 |
| D | - | | - | - | - | ≥ 80 | - |
| D, E | - | | - | - | - | ≥ 80 | ≥ 40 |
| B, D | $H_b < H_d$ | $H_d > H$ | - | ≥ 12 | - | ≥ 80 | - |
| | $H_b > H_d$ | $H_d \leq 1/2H$ | - | ≥ 10 | - | ≥ 80 | - |
| B, D, E | $H_b < H_d$ | $1/2H < H_b \leq H$ | - | ≥ 12 | - | ≥ 100 | ≥ 40 |
| | | $H_b > H$ | Prohibited | | | | |
| | $H_b > H_d$ | $H_d \leq 1/2H$ | - | ≥ 10 | - | ≥ 100 | ≥ 40 |
| | | $1/2H < H_d \leq H$ | - | ≥ 12 | - | ≥ 100 | ≥ 40 |
| | $H_d > H$ | Prohibited | | | | | |




3. When outdoor units are installed in rows.

| H_b H_d | (in) |
|---------------------|-------------|
| $H_b \leq 1/2H$ | $b \leq 10$ |
| $1/2H < H_b \leq H$ | $b \leq 12$ |
| $H_b > H_d$ | Prohibited |



4. When outdoor units are installed one above another.



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.