



## SUBMITTAL DATA

FXE60HP230V1R32AH / FXE60HP230V1R32AO  
60000 BTU/H Unitary Heat Pump Split System

Job Name	Location	Date
Purchaser	Engineer	
Submitted to	For	
Unit Designation	Schedule No.	

		
FXE60HP230V1R32AH	FXE60HP230V1R32AO	WK-010WC1


### GENERAL FEATURES

- AHRI Certificate: 216626011
- High Efficiency DC Inverter Technology
- 24VAC Thermostat Compatible
- Zero Lot Line Design
- New R32 Refrigerant
- WK-010WC1 Programmable Wired Controller Included
- Designed for New Construction or Replacement Market
- Low Ambient Cooling down to -15°C (5°F)
- Low Ambient Heating down to -30°C (-22°F)
- Coil (Outdoor) Copper Tube/Aluminum Fin with Anti-Corrosion Coil Coating (Gold Colored Fin - 1500Hr Salt Spray Rating)
- Coil (Indoor) Copper Tube/Aluminum Fin with Anti-Corrosion Coil Coating (Blue Colored Fin - 500Hr Salt Spray Rating)

## SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

SPECIFICATIONS		FXE60HP230V1R32AH / FXE60HP230V1R32AO		FEATURES & FUNCTIONS SUMMARY		FXE60HP230V1R32AH / FXE60HP230V1R32AO				
System Type		HEAT PUMP		Compressor		Inverter				
<b>SYSTEM PERFORMANCE</b>				Ultra Low Frequency Torque Control				Yes		
Cooling Capacity	Min - Max	Btu/h	27,000 - 59,000		Power Factor Correction				Yes	
	Rated Capacity @95°F	Btu/h	54,000		Compressor Type				Rotary	
Heating Capacity	Min - Max	Btu/h	27,000 - 59,000		Electronic Expansion Valve (EEV)				Yes	
	Rated Capacity @47°F	Btu/h	54,000		Basepan With Electric Heater				Yes	
	Rated Capacity @17°F	Btu/h	43,000		Compressor With Electric Heater				Yes	
	Rated Capacity @5°F	Btu/h	40,000		Fin Coating (Outdoor - Golden & Indoor - Blue)				Acrylic Resin	
SEER2		19.0		Intelligent Defrosting				Yes		
EER2		11.7		Intelligent Preheating				Yes		
HSPF2		9.5		Low Voltage Startup				Yes		
COP @5°F		2.24		Memory/Power Failure Recovery				Yes		
COP @47°F		3.40		Self Diagnosis				Yes		
Cooling Temperature Range	°F	5 - 118		Low Ambient Cooling				No		
Heating Temperature Range	°F	5 - 75		24VAC Thermostat Compatible				Yes		
Refrigerant Type		R32		Indoor Fan Type				Centrifugal		
<b>INDOOR UNIT</b>		<b>FXE60HP230V1R32AH</b>		Multi Fan Speeds				5		
Power Supply	VAC	208-230V / 1Ph / 60 Hz		Auxiliary Electrical Heater				Optional		
Sound Pressure Level	dB(A)	54		A2L Leak Detection Sensor (Indoor)				Factory Installed		
Control Voltage	VAC	24								
MOCP	A	15								
MCA	A	7.7								
Electric Heater (Optional)	kW	6, 9, 12								
Air Flow	CFM	1500								
External Static Pressure (Up to)	In W.c.	1.0								
Dehumidification	pt/hr	9.56								
Drain Piping	in	Φ1×0.05								
External Dimensions (W x H x D)	in	24-13/16 × 21-1/4 × 52								
Package Dimension (W x H x D)	in	27-1/4 × 26 × 54-3/16								
Net Weight	lbs	199.5								
Gross Weight	lbs	218.0								
<b>OUTDOOR UNIT</b>		<b>FXE60HP230V1R32AO</b>								
Power Supply	VAC	208-230V / 1Ph / 60 Hz								
Sound Pressure Level	dB(A)	63								
Control Voltage	VAC	24								
Rated Current Cooling	A	30								
Rated Current Heating	A	32								
MOCP	A	40								
MCA	A	35.5								
Compressor Type		GREE G20 / Double Cylinder / 1 - Stage Inverter								
External Dimensions (W x H x D)	in	35-7/16 × 13-3/8 × 49-5/8								
Package Dimension (W x H x D)	in	40-11/16 × 17-3/8 × 55-3/16								
Net Weight	lbs	214								
Gross Weight	lbs	236								
Refrigerant Charge - R32	oz	148.2								
Additional Charge	oz/ft	0.215								
<b>REFRIGERANT PIPING</b>										
Line Set Size (Liquid - Gas) - Flared Connections	in	3/8 - 3/4								
Pre-Charge Length	ft	31								
Pipe Length (Min - Max)	ft	10 - 98								
Max. Pipe Elevation	ft	49								

## FAN PERFORMANCE



**NOTE:**


1. Above chart CFM ratings are based on dry coil with factory filter installed.
2. For wet coil CFM ratings, multiply the CFM by 0.96 correction factor.

## DIMENSIONS

### INDOOR UNIT

Unit: inch


FXE60HP230V1R32AH	
DIMENSIONS	
A	11-5/8
B	20
H	52
W	24-13/16
D	21-1/4




### OUTDOOR UNIT

Unit: inch

FXE60HP230V1R32AO	
DIMENSIONS	
A	39-3/8
B	16-13/16
C	29-3/8
D	24
E	15-9/16
F	36-1/4
G	14-9/16



## ACCESSORY HEATER AND GENERAL INFORMATION





MODEL	Heat Kit Model	Part Number	Electric Heat (kW)		Min. Circuit Ampacity (A)				Max Fuse or Breaker (A)			
			208V	230V	208V		230V		208V		230V	
FXE60HP230V1R32AH	One Mains Supply											
	320004060223	FLEXA2LHTR06	3.74	4.6	31		33		35		35	
	Two Mains Supply											
						Power A	Power B	Power A	Power B	Power A	Power B	Power A
	320004060224	FLEXA2LHTR09	6.03	7.36	35	13.8	37.5	15	40	15	40	20
	320004060225	FLEXA2LHTR12	7.49	9.2	35	27.5	37.5	30	40	30	40	35

# CLEARANCES


## INDOOR UNIT

Minimum clearance

FRONT	> 24
-------	------



Horizontal Left Configuration - No Modification Needed



Horizontal Right Configuration - Must Relocate Drain Pan

**NOTE:**

Allow a minimum of 24" in front of the unit for service clearance. When installing in an area directly over a finished ceiling (such as an attic), an emergency drain pan is required directly under the unit. **See local and state codes for requirements.** When installing this unit in an area that may become wet, elevate the unit with a sturdy, non-porous material. In installations that may lead to physical damage (i.e. a garage) it is advised to install a protective barrier to prevent such damage. This air handler is designed for a complete supply and return ductwork system.

## OUTDOOR UNIT


Minimum clearance

**NOTE:**

Install the Outdoor Unit **2 Inches** Above the Expected Snow Line

1. When one outdoor unit is to be installed.


A - E	$H_b$ $H_d$ H		(in)				
			a	b	c	d	e
B	-	-	-	$\geq 4$	-	-	-
A, B, C	-	-	$\geq 12$	$\geq 4$	$\geq 4$	-	-
B, E	-	-	-	$\geq 4$	-	-	$\geq 40$
A, B, C, E	-	-	$\geq 12$	$\geq 6$	$\geq 6$	-	$\geq 40$
D	-	-	-	-	-	$\geq 40$	-
D, E	-	-	-	-	-	$\geq 40$	$\geq 40$
B, D	$H_b < H_d$	$H_d < H$	-	$\geq 4$	-	$\geq 40$	-
	$H_b > H_d$	$H_d > H$	-	$\geq 4$	-	$\geq 40$	-
B, D, E	$H_b < H_d$	$H_b \leq 1/2H$	-	$\geq 10$	-	$\geq 80$	$\geq 40$
		$1/2H < H_b \leq H$	-	$\geq 10$	-	$\geq 80$	$\geq 40$
		$H_b > H$	Prohibited				
	$H_b > H_d$	$H_b \leq 1/2H$	-	$\geq 4$	-	$\geq 80$	$\geq 40$
		$1/2H < H_b \leq H$	-	$\geq 8$	-	$\geq 80$	$\geq 40$
		$H_b > H$	Prohibited				



## CLEARANCES


2. When two or more outdoor units are to be installed side by side.

A - E	$H_b$ $H_d$ $H$		(in)				
			a	b	c	d	e
A, B, C	-		$\geq 12$	$\geq 12$	$\geq 40$	-	-
A, B, C, E	-		$\geq 12$	$\geq 12$	$\geq 40$	-	$\geq 40$
D	-		-	-	-	$\geq 80$	-
D, E	-		-	-	-	$\geq 80$	$\geq 40$
B, D	$H_b < H_d$	$H_d > H$	-	$\geq 12$	-	$\geq 80$	-
	$H_b > H_d$	$H_d \leq 1/2H$	-	$\geq 10$	-	$\geq 80$	-
B, D, E	$H_b < H_d$	$1/2H < H_b \leq H$	-	$\geq 12$	-	$\geq 100$	$\geq 40$
		$H_b > H$	Prohibited				
	$H_b > H_d$	$H_d \leq 1/2H$	-	$\geq 10$	-	$\geq 100$	$\geq 40$
		$1/2H < H_d \leq H$	-	$\geq 12$	-	$\geq 100$	$\geq 40$
	$H_d > H$	Prohibited					



3. When outdoor units are installed in rows.

$H_b$ $H_d$	(in)
$H_b \leq 1/2H$	$b \leq 10$
$1/2H < H_b \leq H$	$b \leq 12$
$H_b > H_d$	Prohibited



4. When outdoor units are installed one above another.

