



These fittings are designed to provide minimal pressure drop and uniform strength.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

- Available galvanized.

FIGURE 7068 CROSS

Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1 25	1.315 33.4	2¼ 57	1.3 0.6
1¼ 32	1.660 42.2	2¾ 70	2.1 1.0
1½ 40	1.900 48.3	2¾ 70	2.5 1.1
2 50	2.375 60.3	3¼ 83	2.9 1.3
2½ 65	2.875 73.0	3¾ 95	5.2 2.4
3 80	3.500 88.9	4¼ 108	7.5 3.4
4 100	4.500 114.3	5 127	12.2 5.5
5 125	5.563 141.3	5½ 140	17.6 8.0
6 150	6.625 168.3	6½ 165	28.3 12.8
8 200	8.625 219.1	7¾ 197	48.0 21.8
10 250	10.750 273.1	9 229	70.0 31.8
12 300	12.750 323.9	10 254	110 49.9

Additional sizes available, see Gruvlok Catalog or contact an Anvil Representative.

MATERIAL SPECIFICATIONS

FABRICATED FITTINGS:

- 1"-10"** Carbon Steel, Schedule 40, conforming to ASTM A-53, Grade B
- 12" and above** Carbon Steel, Standard Wall, conforming to ASTM A-53, Grade B

COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	