





HY-725
Tag: _____

**Non-Freeze Wall Hydrant with
NB Box, Integral Vacuum Breaker**

SPECIFICATION: Watts Drainage HY-725 concealed non-freeze key operated wall hydrant with nickel bronze box and door, chrome plated hydrant face, integral vacuum breaker, 3/4"(19) hose connection, 3/4"(19) female x 1"(25) male pipe connection, all bronze head, seat casting and internal working parts, bronze wall casing, and loose key. Complies with ASSE 1019-2004, UPC/IAMPO Listed. Max. operating pressure 125 psi.



-R Round Box for Tilt-Up Construction

Recommended Wall Opening:
5-1/4" x 6-1/4" (133 x 158)

Wall Thickness (Select One)		
Suffix	Description	
-6	6"(152) Thick	☐
-8	8"(203) Thick	☐
-10	10"(254) Thick	☐
-12	12"(305) Thick	☐
-14	14"(356) Thick	☐
-16	16"(406) Thick	☐
-18	18"(457) Thick	☐
-20	20"(508) Thick	☐
-22	22"(559) Thick	☐
-24	24"(610) Thick	☐
Other	Specify _____	☐

Options (Select One or More)		
Suffix	Description	
-K	Cylinder Lock	☐
-88	Wall Clamp	☐
-3	Stainless Steel Box	☐
-CIA	Complete Internal Assembly (Repair Kit)	☐
-R	Round Stainless Steel Box	☐

Job Name _____ Contractor _____

Job Location _____ Contractor's P.O. No. _____

Engineer _____ Representative _____

WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.



Specification Drainage Products

USA: 100 Watts Road, Spindale, NC, 28160-2298; TEL: 828-288-2179 TOLL-FREE: 1-800-338-2581 www.watts.com