

HELIX® 2080



Innovation intertwined with safety. That's the DNA of the Helix® Series. The Helix® 2080 features a 13-gauge aramid and steel blend shell for 360° level A6 cut resistance and Contact Heat level 1 resistance.

A flexible foam nitrile coating provides superior grip and abrasion resistance in dry, oily, and wet situations while maintaining high dexterity and tactility. The 2080 is REACH compliant, meaning its skin-safe and void of harsh chemicals.

Protection zones



Aramid blend shell



ANSI/ISEA 105-2024
CUT

A6



ANSI/ISEA 105-2024
GRAM SCORE

3159



ANSI/ISEA 105-2024
PUNCTURE

3



ANSI/ISEA 105-2024
ABRASION

6



ANSI/ISEA 105-2024
CONTACT HEAT

1



EN388:2016+A1:2018

4X42F



EN 407: 2020

X1XXXX

Attributes

Shell:		13G aramid/steel
Coating:	Material:	Foam nitrile
	Finish:	Textured, slightly tacky
	Weight:	Medium
	Breathability:	Fair
	Flexibility:	Good
Sizes:	Grip:	Dry, oil, or wet
		6/XS through 11/XXL



Product features

- 13-gauge aramid and steel blend shell
- Flexible foam nitrile palm coating provides superior grip and abrasion resistance
- Rates level 1 for EN 407 contact heat resistance
- Made with flame-resistant materials
- Elastic knit wrist helps prevent dirt and debris from entering the glove
- Ultimate dexterity and tactility
- Seamless construction for enhanced comfort and breathability
- Washable
- Vend-packed

Call **1.877.MY ARMOR** or visit **hexarmor.com**

HexArmor® products are cut and puncture resistant, NOT CUT AND PUNCTURE PROOF. Do not use with moving or serrated blades or tools. User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Protection zones are to be used as a general guide. Actual product protection zones may differ. Product features, design, protection zones subject to change. Protected by patents and patents pending.

UVEX SAFETY GROUP GmbH & Co. KG, parent company of HexArmor®, has achieved a Gold EcoVadis Rating, placing us in the top 5% of sustainable suppliers globally.

