



GENESIS SERIES

Low Voltage Cable
Part No. 3116

Description: 18 AWG 6/C STR CL2P, CMP, C(ETL)US FT6
Compliance: UL Standards 13 & 444, NEC Articles 725 & 800, CSA C22.2 No. 214

Construction:

Conductor 18 AWG 19/0.0092" Stranded Bare Copper
Insulation Plenum PVC
Color Blk,Wht,Red,Grn,Brn,Blu
Thickness 0.007" nom.
Diameter 0.060" nom.
Lay Length 5.5" nom.

Jacket
Type Plenum PVC
Color Natural
Thickness 0.015" nom.
Diameter 0.210" nom.
Legend (Ink Print) HONEYWELL P/N 3116 6C18 3038058 (ETL) CL2P OR CMP C(ETL)US FT6 (RoHS)
W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 28 pf/ft nom.
Impedance 72 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating NFPA 262, CSA C22.2 No. 2556 (FT6)