



**Straight Conduit Fitting**

Trade Size (metric designator)	Insulated
3/8 (12)	<b>H0381</b>
1/2 (16)	<b>H0501</b>
3/4 (21)	<b>H0751</b>
1 (27)	<b>H1001</b>
1-1/4 (35)	<b>H1251</b>
1-1/2 (41)	<b>H1501</b>
2 (53)	<b>H2001</b>
2-1/2 (63)	<b>H2501</b>
3 (78)	<b>H3001</b>
3 1/2 (91)	<b>H3501</b>
4 (103)	<b>H4001</b>



**H0751**

Note: 3/8" Liquidtight conduit fitting have 1/2 NPT male threads.  
For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.  
See page Y-95 for technical information.

**45° Conduit Fitting**

Trade Size (metric designator)	Insulated
3/8 (12)	<b>H03841</b>
1/2 (16)	<b>H05041</b>
3/4 (21)	<b>H07541</b>
1 (27)	<b>H10041</b>
1-1/4 (35)	<b>H12541</b>
1-1/2 (41)	<b>H15041</b>
2 (53)	<b>H20041</b>



**H07541**

Note: 3/8" Liquidtight conduit fitting have 1/2 NPT male threads.  
For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.  
See page Y-95 for technical information.

**90° Conduit Fitting**

Trade Size (metric designator)	Insulated
3/8 (12)	<b>H03891</b>
1/2 (16)	<b>H05091</b>
3/4 (21)	<b>H07591</b>
1 (27)	<b>H10091</b>
1-1/4 (35)	<b>H12591</b>
1-1/2 (41)	<b>H15091</b>
2 (53)	<b>H20091</b>
2-1/2 (63)	<b>H25091</b>
3 (78)	<b>H30091</b>
4 (103)	<b>H40091</b>



**H07591**

Note: 3/8" Liquidtight conduit fitting have 1/2 NPT male threads.  
For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.  
See page Y-95 for technical information.

Dimensions in Inches (mm)