

15 Amp, 125, 250 Volts and 277 Volts AC



Connector Bodies

Description	Cord Dia.	Catalog Number		
		15A 125V NEMA L5-15R 0.5 HP	15A 250V NEMA L6-15R 1.5 HP	15A 277V AC NEMA L7-15R 2 HP
Insulgrip connector body, black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL4729C	HBL4579C	HBL4779C
Insulgrip connector body, black and white body, spring termination.	.230"-.720" (5.8-18.3)	HBL4729CST	HBL4579CST	HBL4779CST
All black nylon.	.230"-.720" (5.8-18.3)	HBL4729CBK	—	—
Insulgrip connector body, 8 position angle, black and white nylon. Multiple drive screws.	.325"-.655" (8.3-16.6)	HBL4729CA	—	—
Insulgrip connector body, corrosion resistant, yellow and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL47CM29C	HBL45CM79C	HBL47CM79C
Elastogrip connector body, yellow elastomer, dust tight.	.300"-.655" (7.6-16.6)	HBL2547	—	—
Elastogrip® connector body, yellow elastomer, water/dust tight.	.300"-.655" (7.6-16.6)	HBL25W47**	—	—
Valise® connector body, yellow nylon.	.220"-.660" (5.6-16.8)	HBL4729VY	HBL4579VY	HBL4779VY
Valise connector body, black nylon.	.220"-.660" (5.6-16.8)	HBL4729VBK	HBL4579VBK	HBL4779VBK

Note: See page C-49 for accessories.

Receptacles

Description	Catalog Number		
	HBL4700* HBL47001*	HBL4550* —	HBL4750* —
Duplex, flush, brown RTP face, back and side wired.	HBL4700*	HBL4550*	HBL4750*
Duplex, flush, ivory RTP face, back and side wired.	HBL47001*	—	—
Duplex, flush, brown, spring termination.	HBL4700ST	HBL4550ST	HBL4750ST
Duplex, ring terminal connection.	HBL4700RT*	HBL4550RT*	—
Duplex, isolated ground, flush, orange RTP face, back and side wired.	IG4700A*	IG4550A*	—
Duplex, isolated ground, flush, orange face, spring termination.	IG4700AST	—	—
Duplex, corrosion resistant, yellow RTP face, back and side wired.	HBL47CM00*	—	—
Single flush, black face, spring termination.	HBL4710ST	HBL4560ST	HBL4760ST
Same as HBL4760 without mounting screws, ears. Terminal screws backed out, back and side wired. This item is bulk packed 100 pcs case.	—	—	HBL4760C
Single, ring terminal connection.	HBL4710RT	HBL4560RT	—
Single, isolated ground, flush, orange nylon face, back and side wired.	—	IG4560	—
Single, Isolated ground, flush, orange, spring termination	IG4710ST	—	—
Single, black nylon face mounted on a 4" (101.6) round box cover, back and side wired.	HBL4711	—	HBL4761
Single, panel mount, black nylon face, side wired only, 1.75" or 1.937" (44.5 or 49.2) mounting centers.	—	—	HBL4763
Single, panel mount, black face, spring termination, 1.75" or 1.937" (44.5 or 49.2) mounting centers.	HBL4713ST	HBL4563ST	—

Note: See page C-50 for accessories..

Flanged Receptacles

Description	Catalog Number		
	HBL4715C	HBL4585C	HBL4785C
Insulgrip flanged receptacle, nylon casing, back wired.	HBL4715C	HBL4585C	HBL4785C
Stainless steel casing, brown phenolic.	HBL4715	HBL4585	HBL4785
Corrosion resistant, stainless steel casing, yellow melamine.	HBL47CM15	—	—

Note: See pages C-50 and C-51 for accessories.

HP ratings are AC only.

RTP is an abbreviation for reinforced thermoplastic polyester.

See Section O for additional information on isolated ground devices.

*Supplied with break-off tabs for split circuit wiring.


**Watertight connector body IP55 suitability when closure plug is inserted or when installed and used properly with watertight plug.




HBL4729C




HBL4729CBK




HBL25W47




HBL4729VY



HBL4700



HBL4710



HBL4715



HBL4715C

Dimensions in Inches (mm)