







# METAL AND NON-METALLIC RACEWAY HBL500, HBL700, and HBL750 Series





**U**  
SECTION



## End Fittings

Description	Color	HBL500, HBL700 & HBL750 Series	Description	Color	HBL500, HBL700 & HBL750 Series
<b>Entrance Connector</b> One 3/4 in. KO for panel or conduit connection. One 3/4 in. chase nipple and locknut furnished. 	Ivory White	<b>HBL5786AIVA</b> <b>HBL5786AWA</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	<b>Adjustable Offset Connector</b> Two 1/2 in. KOs for panel or conduit connection. Eliminates offsetting raceway when connecting to surface type panel boxes. One 1/2 in. chase nipple and locknut furnished. 	Ivory White	<b>HBL5786IVA</b> <b>HBL5786AWA</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)
<b>Elbow Box Connector</b> For connecting raceway at right angles to conduit boxes, panel boxes, etc. having 1/2 in. nipple for trade size conduit. 	Ivory White	<b>HBL5783IVA</b> — A: 2.13" (54.05) B: 1.24" (31.50)	<b>Elbow Conduit Connector</b> For connecting raceway at right angles to 1/2 in. trade size conduit or armored cable connectors. 	Ivory White	<b>HBL5784IVA</b> — A: 2.13" (54.05) B: 1.24" (31.50)
<b>Combination Connector</b> For connecting raceway without offsetting to any 3.25 in. (83.00) or 4 in. (102.00) outlet box mounted on the surface with a KO for 1/2 in. trade size conduit. Spring steel bushing eliminates need for conduit nipple and locknut. 	Ivory White	<b>HBL5785AIVA</b> <b>HBL5785AWA</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	<b>Corner Box</b> For connecting HBL500, HBL700 or HBL750 Raceway from ceiling or corner. Each leg of base has 1/2 in. trade size KO. 	Ivory White	<b>HBL5719IVA</b> <b>HBL5719WA</b> A: 2.50" (63.50) B: 2.50" (63.50) C: 2.40" (60.96)

## Fittings

Description	Color	HBL500 Series	HBL700 Series	HBL750 Series
<b>Transition Fitting</b> For transitioning from either Wiremold® V500 to Hubbell HBL500 Raceway or Wiremold V700 to Hubbell HBL700 Raceway or Hubbell HBL750 Raceway. 	Ivory White	<b>HBL500TFIV</b> — A: .65" (16.51) B: .89" (22.61) C: 2.15" (54.61)	<b>HBL700TFIV</b> — A: .78" (19.80) B: .89" (22.61) C: 2.15" (54.61)	<b>HBL750TFIV</b> — A: .98" (24.89) B: .89" (22.61) C: 2.15" (54.61)
<b>Mounting Strap</b> (one- or two-hole) For mounting HBL500, HBL700 or HBL750 Raceway to surface. Convert to one-hole by breaking off at score. 	Ivory White	<b>HBL504IV</b> <b>HBL504W</b> A: .58" (14.73) B: .50" (12.70)	<b>HBL7004IV</b> <b>HBL7004W</b> A: .70" (17.68) B: .50" (12.70)	<b>HBL7504IV</b> <b>HBL7504W</b> A: .90" (22.86) B: .50" (12.70)
<b>Connection Cover</b> To cover potential openings where two lengths of like raceways come together. 	Ivory White	<b>HBL506IV</b> <b>HBL506W</b> A: .60" (15.24) B: .80" (20.31)	<b>HBL7006IV</b> <b>HBL7006W</b> A: .69" (17.40) B: .80" (20.31)	<b>HBL7506IV</b> <b>HBL7506W</b> A: .91" (23.10) B: .80" (20.31)
<b>Bushing</b> Protect wires from potential abrasion. Fits into end of HBL500, HBL700 or HBL750 Raceway. 	Steel*	<b>HBL502B</b> A: .35" (8.83) B: .70" (17.68)	<b>HBL7002B</b> A: .49" (12.50) B: .78" (19.80)	<b>HBL7502B</b> A: .60" (15.24) B: .70" (17.68)

Note: \*Zinc Plated Steel.

Wiremold® is a registered trademark of the Wiremold Company.

Dimensions in Inches (mm)