

Features

Mini-toggles provide for multiple switches in a compact single gang. Maximize control while maintaining function and appearance.

- Low profile, less than 1 inch
- Self-grounding feature is standard
- Combination devices provide compact switches in a single-gang opening
- Smooth toggle action
- Multiple-drive Slot/Phillips/Robertson head screws
- Hi-visibility yellow base for easy installation
- Operating temperature: -20°C to 60°C
- UL Listed, CSA Certified



RC108I



Combination Toggle Switches/Devices

Description	Two (2) Single Pole Switches.	Single Pole Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle.	Single Pole Switch, 2 Pole, 3 Wire, Receptacle.	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb*.
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
Color				
Brown Ivory Light Almond White	RC101 RC101I RC101LA RC101W	RC108TR RC108ITR RC108LATR RC108WTR	RC108 RC108I RC108LA RC108W	RC109 RC109I RC109LA RC109W

Note: See page Tech-10 for Tamper-Resistant description. *Neutral required for pilot light, see page BB-4 for wiring diagram.

Combination Toggle Switches/Devices

Description	Single Pole and Three Way Switch.	Two (2) Three Way Switches.	Three Way Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle.	Three Way Switch, 2 Pole, 3 Wire, Receptacle.	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb*.
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
Color					
Brown Ivory Light Almond White	RC103 RC103I RC103LA RC103W	RC303 RC303I RC303LA RC303W	RC308TR RC308ITR RC308LATR RC308WTR	RC308 RC308I — RC308W	RC309 RC309I — RC309W

Note: See page Tech-10 for Tamper-Resistant description. *Neutral required for pilot light, see page BB-4 for wiring diagram.

Dimensions in Inches (mm)