


Voltage & Conduit Markers

- Identify junction boxes, switches, circuit breakers, raceways, pipe and fuse boxes
- Non-conductive for user safety
- High-adhesion properties with easy removability
- Vinyl-impregnated cloth construction for long-lasting durability
- Resist abrasion, moisture, dirt and oil
- Non-smear, black legend on bright orange background for high visibility



Large:

2-1/4 in. x 9 in. each w/1-3/4 in. type



Medium:

1-1/8 in. x 4-1/2 in. each w/3/4 in. type

Small:

2-1/4 in. x 1/2 in. each w/5/16 in. type

| Legend | Large Cat. No. 1/card | Medium Cat. No. 4/card | Small Cat. No. 18/card |
|--------------|-----------------------|------------------------|------------------------|
| 120/208V | 44-295 | 44-296 | — |
| 277/480V | 44-298 | 44-299 | — |
| 120V | — | 44-353 | — |
| 208V | — | 44-355 | — |
| 240V | — | 44-358 | — |
| 277V | — | — | 44-410 |
| 480V | 44-314 | 44-364 | — |
| DANGER | 44-289 | — | — |
| HIGH VOLTAGE | 44-292 | — | — |

Specifications:

Temperature Range: -40°F to 180°F (-40°C to 82°C)
Adhesion: 45 oz./in. width ultimate

Heavy-Duty Lockout Tags

- High-visibility lettering
- Laminated plastic tags have non-fade legends, resist corrosive and harsh environmental conditions grommet
- Vinyl tags are silk screened with a 7/8 in. metal grommet; fastener included
- Exceeds OSHA's 50-lb. pullout requirement
- Matte finish for easy writing surface

| Legend | Type | Qty. | Cat. No. |
|---|----------------------|---------|----------------|
| Do Not Operate | Heavy-Duty Laminated | 5/card | 44-830 |
| | Heavy-Duty Laminated | 100/box | 44-1830 |
| | Economy Vinyl | 25/bag | 44-848 |
| Do Not Operate - Electricians at Work | Heavy-Duty Laminated | 5/card | 44-832 |
| | Economy Vinyl | 25/bag | 44-843 |
| Do Not Operate - (red striped background) | Heavy-Duty Laminated | 5/card | 44-833 |
| | Heavy-Duty Laminated | 100/box | 44-1833 |
| | Economy Vinyl | 25/bag | 44-849 |

Bilingual Lockout Tags

- Spanish/English tags provide extra safety and information in bilingual situations
- High-visibility lettering
- Laminated vinyl tags with non-fade legends resist corrosive and harsh environmental conditions
- Write-on tag with 7/8 in. grommet can be padlocked to device to help prevent unauthorized removal

| Legend | Qty. | Cat. No. |
|--------------------------|------|---------------|
| Do Not Operate (striped) | 5 | 44-841 |

Lockout Signs

- Resistant to both chemicals and abrasion – protected graphics for indoor and outdoor use

| Legend | Material | Size (In.) | Cat. No. |
|--|-------------------------|------------|---------------|
| OSHA Regulation 36 in. clearance | Self-sticking polyester | 3-1/2 x 10 | 44-877 |
| OSHA Regulation (Bilingual) 36 in. clearance | Self-sticking polyester | 7 x 10 | 44-878 |
| Danger - Breakers Locked Out | Magnetic | 5 x 7 | 44-890 |

Safety Signs

- Resistant to both chemicals & abrasion – protected graphics for indoor & outdoor use



| Legend | Material | Size (In.) | Cat. No. |
|----------------------------------|-------------------------|------------|---------------|
| Danger – High Voltage | Fiberglass | 10 x 14 | 44-862 |
| Danger – High Voltage | Self-Sticking Polyester | 7 x 10 | 44-863 |
| Danger – High Voltage – Keep Out | Fiberglass | 10 x 14 | 44-880 |
| Danger – High Voltage – Keep Out | Self-Sticking Polyester | 7 x 10 | 44-881 |
| Danger – High Voltage – Spanish | Self-Sticking Polyester | 7 x 10 | 44-865 |