


Thermo-Shrink® UF Splice Kits

- Direct burial rated
- 14/3 with and without ground thru 8/3 without ground, UF cable range
- Stretcher kit repairs a 7 in. to 10 in. section damaged or destroyed by a trencher
- 600V Maximum, 105°C rating
- Meets the requirements of the 2002 NEC Code 110-14(b) and UL486D



Description	Cat. No.
 UF Splice Kit - 14-8 AWG, Tubing 1.1 in. x 8 in.	46-400
 UF Stretcher Kit* - 14-8 AWG, Tubing 1.1 in. x 18 in.	46-410

*Stretcher kit connector is 11.5 in.

Thermo-Shrink® Copper Butt Splice Kits



- UL Listed
- Provides a fully-insulated butt splice
- 600V Maximum, 105°C rating



Description	Cat. No.
 Butt Splice Kit – Copper 14-8 AWG	46-404
 Butt Splice Kit – Copper 8-2 AWG	46-405

Thermo-Shrink® Al/Cu Splice Kits

- Direct burial rated, underground splice kits
- Heavy-wall heat shrink tubing with adhesive liner provides complete insulation and protection
- Connector can be used for aluminum and/or copper cable
- Meets the requirements of the 2005 NEC Code 110-14(B)
- 600V maximum, 105°C rating

Description	Cat. No.
 Underground Splice Kit – 8 to 4 AWG, Tubing 3/4 in. x 6 in.	46-401
 Underground Splice Kit – 4 AWG to 1/0, Tubing 1.1 in. x 8 in.	46-402
 Underground Splice Kit – 1/0 to 250 KCMIL, Tubing 1-1/2 in. x 12 in.	46-403

Thermo-Shrink® Heat Shrink Kit

Kit includes:

- HEAT ELITE PRO™ Heat Gun
- Eleven sizes of thin-wall heat shrinkable tubing disks (3/64 in. – 1 in.)
- Small deflector
- Premium T®-Cutter Wire Cutter

Description	Cat. No.
Kit includes: 46-203, 45-123, 45-941 & 46-600 through 46-610	46-007

